

ATTACHMENT L

Geotechnical Site Investigation and Critical Areas/Geohazards Report



GEOTECHNICAL SITE INVESTIGATION AND CRITICAL AREAS / GEOHAZARDS REPORT

**GOOSE PRAIRIE PHOTOVOLTAIC (PV) SOLAR ARRAY PROJECT
STATE ROUTE 24 & DESMARAIS CUTOFF
MOXEE, YAKIMA COUNTY, WASHINGTON**

GNN PROJECT NO. 220-1274

DECEMBER 2020

Prepared for

**OER WA SOLAR 1, LLC
2003 WESTERN AVENUE, SUITE 225
SEATTLE, WASHINGTON**

Prepared by

**GN NORTHERN, INC.
CONSULTING GEOTECHNICAL ENGINEERS
YAKIMA, WASHINGTON
(509) 248-9798**

*Common Sense Approach to Earth and Engineering
Since 1995*



At GN Northern our mission is to serve our clients in the most efficient, cost effective way using the best resources and tools available while maintaining professionalism on every level. Our philosophy is to satisfy our clients through hard work, dedication and extraordinary efforts from all of our valued employees working as an extension of the design and construction team.

December 14, 2020

OER WA Solar 1, LLC
2003 Western Avenue, Suite 225
Seattle, Washington 98121

Attn: Blake Bjornson, Manager, Project Development

**Subject: Geotechnical Site Investigation and Critical Areas / Geohazards Report
Goose Prairie, Photovoltaic (PV) Solar Array Project
State Route 24 & Desmarais Cutoff, Moxee, Yakima County, Washington**

GNN Project No. 220-1274

Dear Mr. Bjornson,

As requested, GN Northern (GNN) has completed a geotechnical site investigation for the proposed Goose Prairie, Photovoltaic (PV) Solar Array Project to be constructed at the ~791-acre site located north and east of the intersection of Desmarais Cutoff and State Route 24 near Moxee, in Yakima County, Washington.


Based on the findings of our subsurface study, we conclude that the site is suitable for the proposed construction provided that our geotechnical recommendations presented in this report are followed during the design and construction phases of the project.


This report describes in detail the results of our investigation, summarizes our findings and presents our recommendations concerning earthwork and the design and construction of foundations for the proposed project. It is important that GN Northern provide consultation during the design phase as well as field compaction testing and geotechnical monitoring services during the earthwork phase to ensure implementation of the geotechnical recommendations.

If you have any questions regarding this report, please contact us at 509-248-9798.

Respectfully submitted,

GN Northern, Inc.


Max Barnett, GIT
Staff Geologist


Karl A. Harmon, LEG, PE
Senior Geologist/Engineer




TABLE OF CONTENTS

| | Page No. |
|---|-----------|
| 1.0 EXECUTIVE SUMMARY | 3 |
| 2.0 PURPOSE AND SCOPE OF SERVICES..... | 4 |
| 3.0 PROPOSED CONSTRUCTION | 6 |
| 4.0 SITE CONDITIONS | 6 |
| 5.0 FIELD EXPLORATION & LABORATORY TESTING..... | 7 |
| 6.0 SOIL INFILTRATION TESTING | 8 |
| 7.0 SUBSURFACE CONDITIONS | 9 |
| 7.1 NRCS SOIL SURVEY | 9 |
| 7.2 GROUNDWATER | 9 |
| 7.3 REGIONAL GEOLOGY | 10 |
| 8.0 CRITICAL AREAS / GEOLOGIC HAZARDS..... | 11 |
| 8.1 SEISMIC HAZARDS..... | 11 |
| 8.2 SITE SLOPE CONDITIONS..... | 12 |
| 8.3 FLOODING AND EROSION | 13 |
| 9.0 SEISMIC DESIGN PARAMETERS | 14 |
| 10.0 SOIL CORROSIVITY TESTING | 15 |
| 11.0 ELECTRICAL RESISTIVITY..... | 17 |
| 12.0 THERMAL RESISTIVITY | 18 |
| 13.0 SUMMARY OF FINDINGS & CONCLUSIONS | 18 |
| 14.0 GEOTECHNICAL RECOMMENDATIONS..... | 21 |
| 14.1 SITE DEVELOPMENT – GRADING..... | 21 |
| 14.2 CLEARING AND GRUBBING | 22 |
| 14.3 SUITABILITY OF THE ONSITE SOILS AS ENGINEERED FILL..... | 22 |
| 14.4 TEMPORARY EXCAVATIONS | 23 |
| 14.5 UTILITY EXCAVATION, PIPE BEDDING AND TRENCH BACKFILL | 23 |
| 14.6 IMPORTED CRUSHED ROCK STRUCTURAL FILL..... | 24 |
| 14.7 COMPACTION REQUIREMENTS FOR ENGINEERED FILL | 25 |
| 14.8 O&M BUILDING FOUNDATION BEARING SUPPORT | 25 |
| 14.9 O&M BUILDING SLAB-ON-GRADE FLOORS..... | 26 |
| 14.10 DRIVEN POSTS PILE FOUNDATION..... | 26 |
| 14.11 DRILLED & GROUTED POSTS PILE FOUNDATION..... | 28 |
| 14.12 FOUNDATION OPTIONS FOR SUBSTATION EQUIPMENT PADS | 28 |
| 14.13 SUBGRADE PROTECTION | 30 |
| 14.14 SURFACE DRAINAGE | 30 |
| 14.15 WET WEATHER CONDITIONS..... | 31 |
| 14.16 SLOPE MAINTENANCE AND EROSION PROTECTION..... | 32 |
| 15.0 CONTINUING GEOTECHNICAL SERVICES..... | 33 |
| 16.0 LIMITATIONS OF THE GEOTECHNICAL SITE INVESTIGATION REPORT | 34 |

APPENDICES

APPENDIX I – VICINITY MAP (FIGURE 1), SITE EXPLORATION MAPS (FIGURES 2 & 3), FAULT AND GEOLOGIC MAP (FIGURE 4), LIQUEFACTION SUSEPTABILITY MAP (FIGURE 5), TOPOGRAPHIC SURVEY
APPENDIX II – EXPLORATORY BORING & TEST PIT LOGS, KEY CHART (FOR SOIL CLASSIFICATION)
APPENDIX III – LABORATORY TESTING RESULTS
APPENDIX IV – SOIL CORROSIVITY TESTING RESULTS
APPENDIX V – RESULTS OF ELECTRICAL RESISTIVITY TESTING
APPENDIX VI – RESULTS OF THERMAL RESISIVITY TESTING
APPENDIX VII – SITE & EXPLORATION PHOTOGRAPHS
APPENDIX VIII – NRCS SOIL SURVEY
APPENDIX IX – WASHINGTON DEPARTMENT OF ECOLOGY WELL LOGS

1.0 EXECUTIVE SUMMARY

GN Northern (GNN) has prepared this executive summary to provide a general overview of this Geotechnical Site Investigation and geologic hazards / critical areas assessment report for the proposed Goose Prairie PV Solar Array Project in Yakima County, Washington. The report itself should be relied upon for information about the findings, conclusions, recommendations, and other concerns. The intent of this report is to assess various geologic hazards that may impact the proposed development and provide our recommendations for mitigation. Our site assessment has been prepared in general accordance with the requirements outlined by Yakima County Critical Areas Ordinance Title 16C, specifically regarding Chapter 16C.08 Geologically Hazardous Areas.

Development on sloping ground poses an inherent risk related to global and local stability of the slopes. Surface soils are generally considered to be erodible. Portions of the project site are identified by Yakima County to lie within areas mapped to be at risk from geology hazards, including steep slopes and erosion hazards.

Our site assessment was performed to identify common geologic conditions in the project region, including soil and bedrock conditions, groundwater, slopes, drainage, erosion, and geologic hazards. A review of selected information pertaining to the subject property and surrounding region was performed that included published technical literature, published geologic maps, available aerial photographs, and previous geotechnical/geologic studies prepared for other sites in the vicinity. Site specific geologic and geotechnical data was obtained from our field exploration program conducted at the project site.

Based on our site evaluation and analyses, our findings indicate that the proposed project may be constructed as planned, provided that the recommendations in this report are incorporated in the final design and construction of this project. The existing site slope conditions are generally considered stable. The proposed development will require appropriate design and construction for proposed reconfigured slopes as well as drainage/erosion control measures to further reduce the risk from geologic site constraints.

The subject property is situated in an area where sheet flow and erosion may occur and near-surface site soils are known to exhibit a risk for erosion. Erosion concerns will require mitigation with appropriate best management practices (BMPs), including proper drainage design as well as

collection and disposal (conveyance) of water to approved points of discharge in a non-erosive manner.

In our professional opinion, the proposed project may be developed as planned, provided that the recommendations in this report are incorporated in the final design and construction. Based on our site evaluation and analysis, the existing native slope conditions are considered stable, however proposed cut and fill slopes for the planned development will require appropriate grading measures as recommended within this report to minimize the risk of slope instability and increase safety factors of the reconfigured slopes. Additionally, based on our evaluation, near surface site soils will not be subject to a significant threat of erosion, provided that the recommendations within this report are incorporated during site grading operations along with appropriate project design, construction, and maintenance.

In our professional opinion, the proposed development, as depicted on the conceptual site layout plan (dated October 28, 2020), will not pose a threat to the public health, safety, or general welfare of the citizens, or increase the risk from geologic hazards on the site or to the surrounding properties, provided the recommendations in this report are followed in the design and construction of the project.

2.0 PURPOSE AND SCOPE OF SERVICES

This report has been prepared for the proposed Goose Prairie PV Solar Array Project to be constructed on the approximately 791-acre site located north and east of the intersection of Desmarais Cutoff and State Route 24 near Moxee, in Yakima County, Washington; site location is shown on the *Vicinity Map* (Figure 1, Appendix I). Our investigation was conducted to collect information regarding subsurface conditions and present recommendations for suitability of the subsurface materials to support the proposed ground-mounted PV solar array facilities and geotechnical design parameters for foundation design and construction.

GN Northern, Inc. has prepared this report for use by the client and their design consultants in the design of the proposed development. Do not use or rely upon this report for other locations or purposes without the written consent of GN Northern, Inc.

Our study was conducted in general accordance with our *Proposal for Geotechnical Site Investigation* dated July 7, 2020; you provided notice to proceed on August 3, 2020 in the form of a signed copy of the *Professional Services Agreement for Geotechnical Engineering Services*.

You provided:

- A topographic survey (*One Energy – Goose Prairie Solar* dated 3/17/2020) for the project site prepared by Gray Surveying & Engineering, Inc. provided via email on August 27, 2020.
- A Google Earth KMZ file showing the site boundaries, the proposed substation location, suggested boring locations, and areas to avoid for subsurface exploration.
- A Statement of Work (SOW) document outlining the minimum requirements for completion of our geotechnical services was provided via email on June 25, 2020.
- An additional electrical resistivity test location provided via email on July 31, 2020.
- A Conceptual Layout Plan (Sheet A-001, dated October 28, 2020) was provided on November 17th depicting the proposed layout of new solar arrays and other planned project improvements.

An initial first round of field exploration, consisting of ten (10) exploratory test pits and three (3) infiltration tests, was completed on August 26, 2020. A second round of exploration, consisting fourteen (14) exploratory borings was conducted between September 15th and the 21st. The various locations of our points of explorations and testing are shown on the *Site & Exploration Maps* (Figures 2 & 3, Appendix I), and detailed boring and test pit logs are presented in Appendix II. Upon receiving the conceptual solar array layout, GNN completed an additional site reconnaissance on November 20th to review site condition and evaluate potential areas of steep slopes that could impact the proposed development.

This report has been prepared to summarize the data obtained during this study and to present our recommendations based on the proposed construction and the subsurface conditions encountered at the site. Results of the field exploration were analyzed to develop recommendations for site development, earthwork, pavements and foundation bearing capacity. Design parameters and a

discussion of the geotechnical engineering considerations related to construction are included in this report.

3.0 PROPOSED CONSTRUCTION

Based on our understanding of the proposed project, a fixed-rack, ground-mounted solar photovoltaic (PV) array system is proposed to be constructed at the project site. Furthermore, we understand that installation of the PV array will require installation of pile foundations, the racking system, solar panels along with associated buried conduit and wiring. Based on our review of the provided KMZ map file of the proposed project site, we understand that an Operation & Maintenance (O & M) building and electrical substation/switch gear facility will be constructed southwest of the intersection of the northern extension of Morris Lane and the eastern extension of Den Beste Road located near the northeast corner of Section 18 (Yakima County Assessor's Parcel No.: 211218-11003). Structural loading information was not available at the time of this report. We further understand that the site will also be developed with various unpaved internal access roadways.

4.0 SITE CONDITIONS

The project site is located along the north side of Highway 24, approximately 7 miles east of the city limits of Moxee, in Yakima County, Washington. Site boundaries include most of Section 18, the most of the southern half of Section 7 and the majority of the SW ¼ of Section 8 Township 12 North and Range 21 East, Willamette Meridian. The site is bound to the east/southeast by Morris Lane, to the south by Highway 24, to the west by Desmarais Cutoff, to the northwest by Den Beste Road, and to the north/northeast by undeveloped/agricultural land. Morris Lane is a north-south aligned gravel road that separates the agricultural land to the east. Den Beste Road is discontinuous on the north side but is mapped as a gravel road. Two gates that access the northern portion of the site are located near the intersection of Den Beste Road and Morris Lane.

The project site is currently undeveloped and has a natural drainage pathway that flows through the site from the northwest to the southwest. The drainage pathway is lined with cobbles and boulders deposits from wash and possible flash flooding events. The site includes a dense growth of grass and sagebrush areas. Based on a brief review of historical aerial photographs, the southwestern portion appears to be historically used for agricultural purposes. Based on the topographic survey

(One Energy – Goose Prairie Solar dated 3/17/2020), the site slopes down to the southwest, with surface elevations ranging from approximately 1,726' near the northeast corner of the site to ~1,386' near the southwestern corner of the site.

5.0 FIELD EXPLORATION & LABORATORY TESTING

Our field exploration included an initial round of test pits, infiltration tests and soil sampling for thermal resistivity testing was completed on August 26, 2020. A local public utility clearance was obtained prior to the field exploration. Ten (10) exploratory test pits and three (3) infiltration test pits were excavated by Valley Septic & Excavation using a Case 580 Super N backhoe to depths ranging from approximately 6 to 11 feet below existing ground surface (BGS). The test pits were logged by a GNN field geologist. Upon completion, all excavations were loosely backfilled with excavation spoils. Secondary subsurface exploration consisted of fourteen (14) exploratory borings to depths of ~20 to 41.5 feet BGS, drilled by Western States Soil Conservation, Inc. using a CME 55 track mounted drill rig. Boring, test pit, and infiltration test locations are shown on the *Site & Exploration Maps* (Figures 2 & 3).

The soils observed during our field exploration were classified according to the Unified Soil Classification System (USCS), utilizing the field classification procedures as outlined in ASTM D2488. A copy of the USCS Classification Chart is included in Appendix II. Photographs of the site and exploration are presented in Appendix V. Depths referred to in this report are relative to the existing ground surface elevation at the time of our investigation. The surface and subsurface conditions described in this report are as observed at the time of our field investigation.

Representative samples of the subsurface soils obtained from the field exploration were selected for testing to determine the index properties of the soils in general accordance with ASTM procedures. The following laboratory tests were performed:

Table 1: Laboratory Tests Performed

| Test | To determine |
|--|--|
| Particle Size Distribution (ASTM D6913 & D422) | Soil classification based on proportion of sand, silt, and clay-sized particles |
| Natural Moisture Content (ASTM D2216) | Soil moisture content indicative of in-situ condition at the time samples were taken |

| | |
|--|--|
| Moisture-density Relationship (ASTM D698 Standard Proctor test) | The optimum moisture content for compacting soil and the maximum dry unit weight (density) for a given compaction effort |
| Soil pH (ASTM G51) | Electrometric procedure for measuring pH in soils |
| Soil Resistivity (ASTM G-187) | Measurement of soil resistivity to assist in the determination of soil's corrosive nature |
| Redox Potential (ASTM D1498-76) | Electrometric measurement of oxidation-reduction potential (ORP) in water |
| Chloride and Sulfate (ASTM D4327) | Determination of chloride and sulfate inorganic ions in soil |
| Sulfide (Acetate Paper) | Determination of the total Sulphur content of soil |

Results of the laboratory soil testing are included in Appendix III and soil corrosivity laboratory tests are included in Appendix IV attached to the end of the report.

6.0 SOIL INFILTRATION TESTING

Infiltration testing was performed within shallow test pits at the three selected locations (see Figures 2 & 3) using a single ring infiltrometer consisting of a 10-inch diameter steel pipe driven into the ground at the test depth. After an initial pre-soak period, a constant water level was maintained in the ring with the use of a float valve and timed intervals of the water demand volumes were recorded. Continuous readings of the infiltration rates of water volumes required to maintain the constant head were recorded until a relatively constant rate was achieved. The following table presents the results of infiltration tests performed, indicative of the infiltration characteristics of the soils encountered at the test locations/depths using the specified test method:

| Test ID | Test Location (Approx. GPS Coords.) | Test Depth (BGS) | Soil Tested | Field Measured Soil Infiltration Rate |
|---------|--|---------------------|-----------------------|---------------------------------------|
| P-1 | 46.534377°, -120.231318° | 3 feet | Silt with Gravel (ML) | 0.9 inches/hour |
| P-2 | 46.535864°, -120.234161° | 3 feet | Silt (ML) | 0.2 inches/hour |
| P-3 | 46.522976°, -120.238195° | 3 feet | Silt (ML) | 0.1 inches/hour |

An appropriate factor of safety should be applied to the field infiltration rates to determine long-term design infiltration rates. Determination of safety factors for long-term infiltration design should consider the following: pretreatment, potential for bio-fouling, system maintainability,

horizontal and vertical variability of soils. A factor of safety of 2 to 3 is considered appropriate for long-term design.

7.0 SUBSURFACE CONDITIONS

Based on the findings of our field exploration, subsurface soil conditions across the site generally include a layer of aeolian (wind-blown) silts and sands atop cemented gravels and deeper siltstone and sandstone layers. These fine- to coarse-grained sedimentary rocks are mapped as the Ellensburg Formation (*Source: Geologic Map of the East Half of the Yakima 1:100,000 Quadrangle, Washington*). Interbedded gravelly layers were encountered within borings B-1, B-5, & B-7. Shallow gravel units were classified as Silty Gravel with Sand (GM) with large amounts of caliche. This hard caliche unit resulted in excavation (bucket) refusal at all test pit locations except for test pits TP-1 & TP-3. Borings extended deeper into dense and very dense cemented silts and sands. Logs of exploratory borings and test pits with detailed descriptions and stratification of the soils encountered are included in Appendix II.

7.1 NRCS Soil Survey

The soil survey map of the site prepared by the Natural Resources Conservation Service (NRCS) identifies the site soils as *Finley cobbly fine sandy loam*, *Kiona stony silt loam*, *Licksillet very stony silt loam*, *Moxee silt loam*, *Ritzville silt loam*, *Willis silt loam*. These soils generally are sourced from parent material described as *loess*, *alluvium*, *residuum*, and *colluvium derived from basalt*. The typical soil profile for these units are described as *silt to cobbly loam atop cemented material*, *very gravelly loam*, and *unweathered bedrock*. Based on the NRCS map (Appendix VI), this soil unit generally consists of *well drained* materials.

7.2 Groundwater

Groundwater was not encountered within the borings and test pits at time of our exploration to a maximum depth of approximately 41 feet BGS. We reviewed the Washington Department of Ecology (DOE) Well Log database to estimate groundwater levels in the site vicinity based on nearby wells. Our review of three nearby well log indicates depth of groundwater in the site vicinity to be on the order of 100 feet BGS or greater (see Appendix VII). There is a potential for surface water percolating and perching atop the hard caliche layer. Groundwater levels likely

fluctuate throughout the year with irrigation, precipitation, drainage, and regional pumping from wells, typically highest during the irrigation season and decreasing thereafter.

With regard to Yakima County Critical Areas Ordinance, Chapter 16C.09, addressing Critical Aquifer Recharge Areas (CARAs), due to the noted subsurface soil and rock conditions that prevail across the project site and significant depth to static groundwater conditions, the risk of groundwater contamination resulting from the proposed development is nil provided appropriate stormwater management facilities are incorporated into the project design.

7.3 Regional Geology

The large and irregularly shaped subject site is located within the Moxee Valley on the southern flanks of Yakima Ridge, north of the Rattlesnake Hills approximately 7 miles east of Moxee, Washington. The approximately 791-acre proposed solar project site extends from Highway 24 to approximately 1 ½ miles north and encompasses the northern portion of Section 18, the southeastern portion of Section 7, and the southwestern portion of Section 8.

The Moxee Valley is located in the Yakima Fold Belts sub-province, formed by north–south compression within the Columbia Basin physiographic province of southeastern Washington. The Columbia Basin Plateau is a broad plain situated between the Cascade Range to the west and the Rocky Mountains to the east. The Columbia Plateau is often called the Columbia Basin for the reason that it forms a broad lowland surrounded by mountains. The Columbia Plateau was formed by a thick sequence of folded Miocene-Age (17-6 million years BYP) tholeiitic basalt flows and interbedded sediments, known as the Columbia River Basalt Group (CRBG), which erupted from fissures in north-central and northeastern Oregon, eastern Washington, and western Idaho. Published geologic maps of the site vicinity generally depict Miocene basalts of the Columbia River Basalt Group (CRBG) in higher elevations north of the site along the Yakima Ridge as well as the Rattlesnake hills to the south. The subject site is situated on alluvial fan deposits underlain by middle to upper Miocene continental sedimentary deposits and rock of the Ellensburg Formation. Overlying sediments include relatively thin surficial deposits consisting of Plio-Pleistocene loess, including silt and fine-grained sands.

8.0 CRITICAL AREAS / GEOLOGIC HAZARDS

Geologic hazards that may affect the development include seismic hazards (ground shaking, surface fault rupture, soil liquefaction, and other secondary earthquake-related hazards), slope instability, flooding, ground subsidence, and erosion. A discussion follows on the specific hazards to this site.

8.1 Seismic Hazards

8.1.1 Surface Fault Rupture: For the purposes of this report, an active fault is defined as a fault that has had displacement within the Holocene epoch or last 11,000 years. Due to the lack of known active fault traces in the immediate site vicinity, surface fault rupture is unlikely to occur at the project site. While fault rupture would most likely occur along previously established fault traces, future fault rupture could occur at other locations.

8.1.2 Soil Liquefaction: Liquefaction is the loss of soil strength from sudden shock (usually earthquake shaking), causing the soil to become a fluid mass. In general, for the effects of liquefaction to be manifested at the surface, groundwater levels must be within 50 feet of the ground surface and the soils within the saturated zone must also be susceptible to liquefaction. Based on the published *Liquefaction Susceptibility Map of Yakima County, Washington* (dated September 2004- Figure 5 in Appendix I) prepared by Washington State Department of Natural Resources (DNR), the site is mapped within an area of very low to low liquefaction susceptibility with a few areas mapped as bedrock. Based on our site-specific evaluation, the risk of liquefaction at the subject site is considered very low.

8.1.3 Secondary Seismic Hazards: Secondary seismic hazards include tsunamis, and seiches. The site is far inland, so the hazard from tsunamis is non-existent. The potential hazard from seiches is also nil due to the lack of nearby surface water bodies and the noted low magnitudes of potential seismic shaking.

8.1.4 Seismic Conditions: The Yakima region is generally not considered to be located within an area of high seismic activity. There are no confirmed major faults in the region capable of producing strong earthquakes. Anticipated ground motions in the region due to seismic activity along faults in other parts of the Northwest are relatively low.

The two largest crustal earthquakes felt in the state of Washington included the 1872, M 6.8 quake near Lake Chelan and the 1936, M 6.0 Walla Walla earthquake. The following list provides information regarding historic earthquakes within the past 50 years for epicenters within 100 miles of the subject site (data from www.earthquake.usgs.gov) listed by magnitude:

Table 2: Earthquakes within 100-miles of site

| Date of Event | Magnitude | Distance from site (miles) |
|----------------------|------------------|-----------------------------------|
| May 18, 1980 | 5.7 | 96.7 |
| May 28, 1981 | 5.5 | 55.7 |
| December 12, 1989 | 4.9 | 89.9 |
| May 16, 1980 | 4.7 | 96.5 |
| May 13, 1981 | 4.6 | 97.1 |
| October 8, 2006 | 4.5 | 68.9 |

8.2 Site Slope Conditions

Native slopes throughout the project site generally descend at gradients ranging from approximately less than 5% to some limited areas at greater than 75%. Site elevations range from approximately 1,386' to 1,726', for a total relief within the project boundaries of about 340 feet.

Detailed field reconnaissance of the project site was performed on August 26th and November 20th to observe site conditions and correlate the information gathered from our preliminary research. During our reconnaissance we looked for common geomorphic features of landslides as well as indications of possible signs demonstrating recent activity and instability of slide masses. Aside from noted area of potential ongoing sluffing along the over-steeped erosional slopes along the drainage wash that crosses the northern portion of the site, no evidence of any significant slope instability within the native conditions was noted at the site.

Based on the findings from our subsurface field explorations, detailed site reconnaissance, and desktop study, we can conclude that the existing native (undisturbed) site slopes are generally considered to be grossly stable with expected factors of safety against movement to be well above recommended minimums for development. The existing native onsite vegetation serves to provide some protection from shallow surficial instability and erosional forces. Ongoing long-term raveling/spalling of the exposed gravely/cobbly incised sides of the noted drainage channel will continue. No further stability analyses of the existing slope conditions appear warranted.

Based on our review of the conceptual site layout and the topographic survey, it appears that the planned layout generally avoids any areas of significantly steep slopes. It shall be noted that construction of new solar arrays or other ancillary structures should be avoided on areas of existing native slopes steeper than 2H:1V. Any proposed reconfigured cut or fill slopes should be constructed with appropriate geotechnical engineered grading practices, including keying and benching and proper placement of engineered fill at maximum gradients not to exceed 2H:1V. The design team shall prepare an overlay of the final layout on the final grading plan to ensure compliance with this requirement. GNN is available for additional review and consultation if necessary.

8.3 Flooding and Erosion

The subject property is not located in an area mapped by FEMA regarding flooding concerns. Portions of the subject property are however situated in areas where sheet flow and erosion may occur. Additionally, the project site includes a number of natural downslope drainages/gullies crossing the proposed development. A significant erosional drainage gully or wash extends from the northeast portion of the site and then drains approximately east to west through the site near the northern boundary of Section 18. The incised drainage is depicted on USGS maps as an *intermittent* stream (seasonal) / *ephemeral* stream (flow only after significant precipitation). The noted drainage path incises through the alluvial fan deposits. Yakima County has mapped the area along the well-defined drainage as geologically hazardous that is susceptible to “*alluvial fan/flash flooding*”.

Erosion susceptibility from water is based on several factors including the intensity of rainfall and runoff, soil erodibility, length and steepness of slopes, and surface condition. The erodibility factor of the soils is a measure of the soils resistance to erosion based on its physical characteristics. Typically, very fine sand, silt and clay soils are generally susceptible to erosion. Based on site specific field exploration, observations, and laboratory testing, the surficial soil exposed at the project site consists primarily of sandy silt. The near surface site soils are known to exhibit a moderate to severe potential for erosion.

Soil erodibility is only one of several factors affecting the erosion susceptibility. Soil erosion by water also increases with the length and steepness of the site slopes due to the increased velocity of

runoff and resulting greater degree of scour and sediment transport. Appropriate erosion & sediment control and drainage plans shall be prepared by the project civil engineer with the final construction drawings.

The need for and design of flood control devices and erosion protection measures is within the purview of the design Civil Engineer. Based on a review of the conceptual layout for the proposed solar array facility, we understand that no development is planned within or in sufficiently close proximity to the noted incised drainage to pose a risk from potential flooding events. In general, erosion should be mitigated with best management practices (BMPs) consisting of proper drainage design including collecting and disposal (conveyance) of water to approved points of discharge in a non-erosive manner, installation of check dams, placement of vegetative covers and erosion control mats on slope surfaces. Appropriate project design, construction, and maintenance will be necessary to mitigate the risk from site erosion.

9.0 SEISMIC DESIGN PARAMETERS

To estimate the mapped maximum credible earthquake (MCE) spectral response accelerations with 5 percent damping at short periods (S_s) and at the 1-second period (S_1), the site's latitude and longitude coordinates were entered into the USGS Earthquake Ground Motion Application which computes values based on smoothing and averaging of the spectral response acceleration contour map data included in the IBC (International Code Council, 2015). As per the *2015 International Building Code* (IBC), a Site Class 'D' may be used for seismic design purposes. Site Class 'D' corresponds to 'still soil'.

We anticipate that the seismic design of this project will follow the procedures in 2015 IBC (ICC 2015) and ASCE 7-10 (ASCE/SEI 2010). However, we have also provided the design parameters in accordance with ASCE 7-16 (ASCE/SEI 2016). We obtained the seismic parameter from the National Seismic Hazard Maps. The following tables present the recommended seismic design parameters per ASCE 7-10 and ASCE 7-16 for a code-based response spectrum with a return period of 2,475 years.

**IBC 2015 Design Response
Spectra Parameters**

| Seismic Design Parameter | Value (unit) |
|--------------------------|------------------|
| S_S | 0.470 (g) |
| S_1 | 0.192 (g) |
| F_a | 1.424 (unitless) |
| F_v | 2.030 (unitless) |
| S_{MS} | 0.669 (g) |
| S_{M1} | 0.391 (g) |
| S_{DS} | 0.446 (g) |
| S_{D1} | 0.260 (g) |
| PGA | 0.193 (g) |
| F_{PGA} | 1.414 |
| PGA_M | 0.273 (g) |
| PGA_D | 0.6 |

**IBC 2018/ASCE7-16 Design
Response Spectra Parameters**

| Seismic Design Parameter | Value (unit) |
|--------------------------|------------------|
| S_S | 0.438 (g) |
| S_1 | 0.182 (g) |
| F_a | 1.449 (unitless) |
| F_v | 2.235 (unitless) |
| S_{MS} | 0.635 (g) |
| S_{M1} | 0.408 (g) |
| S_{DS} | 0.424 (g) |
| S_{D1} | 0.272 (g) |
| PGA | 0.195 (g) |
| F_{PGA} | 1.410 |
| PGA_M | 0.275 (g) |
| PGA_D | 0.5 |

S_S = MCE spectral response acceleration at short periods

S_1 = MCE spectral response acceleration at 1-second period

F_a = Site coefficient for short periods

F_v = Site coefficient for 1-second period

S_{MS} = MCE spectral response acceleration at short periods as adjusted for site effects

S_{M1} = MCE spectral response acceleration at 1-second period as adjusted for site effects

S_{DS} = Design spectral response acceleration at short periods

S_{D1} = Design spectral response acceleration at 1-second period

PGA = MCE_G peak ground acceleration

F_{PGA} = Site amplification factor at PGA

PGA_M = Site modified peak ground acceleration

PGA_D = Factored deterministic acceleration value

10.0 SOIL CORROSIVITY TESTING

The potential corrosive environment for metal (ductile iron or steel piping) placed beneath the ground at the project site was evaluated based on data collected during our field exploration and laboratory analytical testing based on the parameters presented in “Corrosion of Building Materials” by Dietbert Knofel. Soil samples were collected at depths of approx. 1.5 and 4 feet BGS from test pits TP-1 (substation), TP-3 (northeastern portion) and TP-8 (most southern test pit) and shipped to AMTest for laboratory testing. The corrosion suite includes pH, electrical resistivity, Redox potential, chloride, sulfate, and sulfide. The results of laboratory testing are attached in Appendix IV and summarized as follows:

Table 3: Summary of Corrosivity Testing Results

| Sample, Ft. BGS | pH | Resistivity (ohms cm) | Redox Potential | Water Soluble Chloride (µg/g) | Water Soluble Sulfate (µg/g) | Sulfide |
|-----------------|------|-----------------------|-----------------|-------------------------------|------------------------------|----------|
| TP-1 @ 4' | 8.16 | 3,300 | 359 | 30 | <10 | Negative |
| TP-3 @ 4' | 8.35 | 2,400 | 379 | 64 | <10 | Negative |
| TP-8 @ 1.5' | 7.33 | 8200 | 414 | <10 | 17 | Negative |

The electrical resistivity of a soil is the measure of resistance to the flow of electrical current. Corrosion of buried metal is an electrochemical process in which the amount of metal loss due to corrosion is directly proportional to the flow of electrical current (DC) from the metal into the soil. As the resistivity of the soil decreases, the corrosivity generally increases. The following correlation between soil resistivity and expected corrosion attack is used in our assessment of soil aggressivity (from Dietbert Knofel page 64, Table 6.7; Source: Waters et al.):

Specific Resistivity (ohm-cm)

<1000
1000 to 3,000
3,000 to 5,000
5,000 to 10,000
10,000 to 20,000
>20,000

Exposed Corrosion Attack

very strongly aggressive
strongly aggressive
aggressive
moderately aggressive
slightly aggressive
virtually nonaggressive

Electrical resistivity test results indicate that the near surface soil conditions are “strongly to moderately aggressive” towards iron and other buried metal. Based on a scale published in “Corrosion of Building Materials”, the results of other parameters used in the determination of soil aggressivity i.e. soil type, water content, pH, redox potential, sulfate, chloride and sulfide indicate subsurface soils to be slightly aggressive. Other soils found across the project site may be more, less, or of a similar corrosive nature.

We recommend that additional near surface soil samples be collected from various locations across the site for laboratory testing, this would help better define the potential risk for buried metal corrosion and the need for corrosion protection.

Water Soluble Sulfates: Sulfate and other salts can attack the cement within concrete causing weakening of the cement matrix and eventual deterioration by raveling. This attack is in the form of a chemical attack, a chemical reaction between the sulfate and the cement used in the concrete.

According to ACI 318, if sulfate concentrations exceed 1000 ppm there will be special requirements.

The concentration of water-soluble sulfates measured in samples tested ranges from less than 10 ppm to 17 ppm. This concentration of water-soluble sulfates represents a negligible degree of sulfate attack on concrete exposed to these soils. The degree of attack is based on a range of negligible, positive, severe and very severe as presented in the U.S. Bureau of Reclamation Concrete Manual. We recommend that the use of ASTM Type I or Type II cement is appropriate for the project.

Chloride Ion Concentration: Chloride ions can cause corrosion of reinforcing steel. For this project, the testing results suggest a low chloride ion concentration. ACI 318 provides commentary relative to the effects of chlorides present in the soil from both internal and external sources. It is possible that long term saturation of foundations with chloride rich water could allow the chloride access to the reinforcing steel. Therefore, if the site is adequately drained in accordance with sound engineering practice and the applicable codes, this should be a low threat. A minimum concrete cover of cast-in-place concrete should be in accordance with Section 7.7 of the 2007 edition of ACI 318. Additionally, the concrete should be thoroughly vibrated during placement. The information provided above should be considered preliminary. These values can potentially change based on several factors, such as importing soil from another job site and the quality of water used during grading.

11.0 ELECTRICAL RESISTIVITY

Soil resistivity testing was performed at the substation location and the alternate test site in the northeast corner of the site on September 2, 2020.

The electrical resistivity sounding technique measures the differences in the electrical properties of geologic materials. These differences can result from variations in lithology, water content, and pore-water chemistry. The method involves transmitting an electric current into the ground between two electrodes and measuring the voltage between two other electrodes. The direct measurement is the apparent resistivity of the area beneath the electrodes. The measurements include deeper layers as the electrode spacing is increased.

Two sets of resistivity testing were performed at each location using the Wenner Four-Electrode Method. The data was acquired with an AGI Super Sting resistivity meter, along N-S and E-W directions. Eight (8) different pin spacings were used for each of the two traverses. The current and potential electrodes were driven to a uniform depth not exceeding more than 10% of the pin spacing. The four pins/electrodes were equally spaced for each set of pin spacings. Ground temperature and the moisture content of the ground (dry, moist, wet) at the time of the resistivity test was recorded. Care was taken to avoid traverses that are parallel to transmission lines or buried metallic or concrete structures.

Apparent Resistance measurements trend downwards with increased pin spacings. The data measured confirms this trend. The data indicate low resistivity soils. The type of soil, moisture content, depth of groundwater, temperature, and soil pH (mineral/salt content) affect its resistivity.

A map showing the N-S and E-W resistivity traverses is included in Appendix I, Figures 2 and 3, and the resistivity measurements are presented in Appendix V.

12.0 THERMAL RESISTIVITY

Soil samples were collected at depth of 3 feet BGS at locations TRT #1 (northern portion), TRT #2 (substation location) and TRT #3 (southern portion) for thermal resistivity analysis and shipped to Geotherm USA. The testing was conducted in accordance with IEEE Standard 442-2017. Results of the thermal resistivity testing are shown in Appendix VI.

13.0 SUMMARY OF FINDINGS & CONCLUSIONS

Conditions imposed by the proposed development have been evaluated on the basis of assumed elevations and engineering characteristics of the subsurface materials encountered in the exploratory borings and test pits, and their anticipated behavior both during and after construction. The following is a summary of our findings, conclusions and professional opinions based on the data obtained from a review of selected technical literature and the site evaluation.

- Based on the findings of this geotechnical evaluation and our understanding of the proposed development, from a geotechnical perspective, it is our opinion that the site is suitable for the proposed development, provided the soil design parameters and site-specific recommendations in this report are followed in the design and construction of the project.

- Final design plans for the proposed development, including grading, drainage and finished elevations, were not provided at the time of this report. Once the plans are finalized, GNN shall be provided an opportunity to review final design plans to provide revised recommendations if/as necessary.
- GNN's findings and recommendations presented in this report are based on a limited number of widely spaced points of subsurface exploration across the project site. Due to the large nature of the site, variations in soil, bedrock, and/or groundwater conditions could exist between and beyond the areas observed and explored and may not become evident until construction.
- We recommend that additional near surface soil samples be collected from various locations across the site for laboratory testing, this would help better define the potential risk for buried metal corrosion and the need for corrosion protection.
- Site soils include generally a relatively thin layer of silty/sandy loess soil atop a shallow unit of cemented gravelly soil stratum underlain at depth by sedimentary sandstone and siltstone known as the Ellensburg Formation.
- Groundwater was not encountered within any of our explorations to a maximum depth of approximately 41 feet BGS and is not considered a factor in the design and construction at the site.
- The underlying geologic condition for seismic design is site class 'D'. The *minimum* seismic design should comply with the *2015 or 2018 International Building Code (IBC)* and *ASCE 07-10 or ASCE 07-16, Minimum Design Loads for Buildings and Other Structures*.
- The onsite silty/sandy soils, free of oversize rocks (>5 inches) and any deleterious materials, are generally suitable for reuse as engineered fill and utility trench backfill. Excavated material derived from the caliche/cemented soil unit may be considered suitable for backfill provided the material is processed and screened to create a 5-inch minus well-graded material.
- The upper fine-grained silts and sands aeolian/loess deposits (wind-blown deposits) will require over-excavation and recompaction to minimize the risk of soil collapse.
- The proposed O & M building may be supported on conventional shallow foundations bearing directly on the native caliche subgrade in accordance with the recommendations of this report.

- Site grading shall incorporate the requirements of IBC 2015, Appendix J *Grading*.
- Upon completion, all test pit excavations were loosely backfilled with excavation spoils. The contractor is responsible to locate the test pits to re-excavate the loose soils and re-place as compacted engineered fill.
- The presence of relatively shallow caliche that prevail across the majority of the project site, particularly the southern portion located south of Den Beste Road, poses a challenge/difficulty for excavation with traditional earthwork equipment. Appropriately capable rippers and/or excavator-mounted hoe-rams will be required for excavation into/through the caliche layer.
- Construction of solar arrays or other ancillary structures should be avoided on areas of existing native slopes steeper than 2H:1V. Any proposed reconfigured cut or fill slopes should be constructed with appropriate geotechnical engineered grading practices, including keying and benching and proper placement of engineered fill at maximum gradients not to exceed 2H:1V.
- The subject site is situated on alluvial fan deposits underlain by sedimentary deposits and rock of the Ellensburg Formation. Overlying sediments include relatively thin surficial deposits consisting of Plio-Pleistocene loess, including silt and fine-grained sands.
- The near-surface site soils are susceptible to wind and water erosion when exposed during grading operations. Preventative measures and appropriate BMPs to control runoff and reduce erosion should be incorporated into site grading plans, with particular attention along the numerous noted onsite natural drainage pathways throughout the project site.
- All slope faces shall be protected with appropriate erosion control measures (BMPs) to insure long-term surficial stability.
- Yakima County has mapped the area along the noted well-defined drainage as geologically hazardous and susceptible to “*alluvial fan/flash flooding*”. It should be understood that there is no geologic hazards directly associate with the project site situated on alluvial fan deposits. However, development within the drainage should be avoided due to the potential risk of flooding. Based on a review of the conceptual layout for the proposed solar array facility, we understand that no development is planned within or in sufficiently close proximity to the noted incised drainage to pose a risk from potential flooding events.

- *In our professional opinion, the proposed development at the site will not pose a threat to the public health, safety, or general welfare of the citizens, or increase the risk from geologic hazards at the site or to surrounding properties, provided the recommendations in this report are followed in the design and construction of the project.*

14.0 GEOTECHNICAL RECOMMENDATIONS

The following geotechnical recommendations are based on our current understanding of the proposed project. The report is prepared to comply with the 2015 International Building Code Section 1803, Geotechnical Investigations, and as required by Subsection 1803.2, Investigations Required. Please note that Soil Design Parameters and Recommendations presented in this report are predicated upon appropriate geotechnical monitoring and testing of the site preparation and foundation and building pad construction by a representative of GNN's Geotechnical-Engineer-of-Record (GER). Any deviation and nonconformity from this requirement may invalidate, partially or in whole, the following recommendations. We recommend that we be engaged to review grading and foundation plans in order to provide revised, augmented, and/or additional geotechnical recommendations as required.

14.1 Site Development – Grading

Site grading shall incorporate the requirements of IBC 2015 Appendix J. The project GER or a representative of the GER should observe site clearing, grading, and the bottoms of excavations before placing fills. Local variations in soil conditions may warrant increasing the depth of over-excavation and recompaction. Seasonal weather conditions may adversely affect grading operations. To improve compaction efforts and prevent potential pumping and unstable ground conditions, we suggest performing site grading during dryer periods of the year.

Soil conditions shall be evaluated by in-place density testing, visual evaluation, probing, and proof-rolling of the imported fill and re-compacted on-site soil as it is prepared to check for compliance with recommendations of this report. A moisture-density curve shall be established in accordance with the ASTM D1557 method for all onsite soils and imported fill materials used as structural fill.

To mitigate the risk of soil collapse, over-excavation and recompaction of the upper fine-grained silts and sands (wind-blown loess deposits) is required if encountered under spread footings, slabs and hardscapes areas.

The contractor shall locate all test pits indicated in the Geotechnical Site Investigation Report within the limits of Work. At each test pit, re-excavate soils loosely backfilled during prior investigation and backfill the excavation with onsite fill soils placed as engineered fill.

Earthwork during wet weather should be avoided, if possible. If earthwork operations cannot be avoided in wet weather, comply with recommendations presented in Section 13.15 “Wet Weather Conditions”. If earthwork occurs during wet weather, expect disturbance to subgrades and expect to perform corrective work to repair disturbed subgrades.

14.2 Clearing and Grubbing

At the start of site grading, any vegetation, large roots, any non-engineered/artificial fill, and any abandoned underground utilities shall be removed from the proposed building and structural areas. The surface shall be stripped of all topsoil and/or organic growth (vegetation) that may exist within the proposed structural areas. The topsoil and organic rich soils shall either be stockpiled on-site separately for future use or be removed from the construction area. Depth of stripping can be minimized with real-time onsite observation of sufficient removals. Areas disturbed during clearing shall be properly backfilled and compacted as described below.

14.3 Suitability of the Onsite Soils as Engineered Fill

The native onsite silty/sandy soils, free of oversize rocks (>5 inches) and deleterious materials, are generally suitable for reuse as engineered fill and utility trench backfill. Excavated material derived from the cemented gravelly unit may be considered suitable for backfill provided the material is processed and screened to create a 5-inch minus well-graded material meeting the following grading limits:

| Sieve Size | Percent Passing |
|-------------------|------------------------|
| 5" | 100 |
| ¾" | 70 |
| #4 | 35-65 |
| #200 | Less than 8 |

Suitable onsite soils shall be placed in maximum 8-inch lifts (loose) and compacted to at least 95% relative compaction (ASTM D1557) near its optimum moisture content. The near-surface silty/sandy soils are considered moisture-sensitive; therefore, compaction of the suitable onsite soils shall be performed within a range of $\pm 2\%$ of optimum moisture to achieve the proper degree of compaction.

14.4 Temporary Excavations

It shall be the responsibility of the contractor to maintain safe temporary slope configurations since the contractor is at the job site, able to observe the nature and conditions of the slopes and be able to monitor the subsurface conditions encountered. Unsupported vertical cuts deeper than 4 feet are not recommended if worker access is necessary. The cuts shall be adequately sloped, shored or supported to prevent injury to personnel from caving and sloughing. The contractor and subcontractors shall be aware of and familiar with applicable local, state and federal safety regulation including the current OSHA Excavation and Trench Safety Standards, and OSHA Health and Safety Standards for Excavations, 29 CFR Part 1929, or successor regulations.

According to chapter 296-155 of the Washington Administrative Code (WAC), it is our opinion that the near-surface soil encountered at the site is classified as Type C soils. We recommend that temporary, unsupported, open cut slopes shall be no steeper than 1.5 feet horizontal to 1.0 feet vertical (1.5H:1V) in Type C soils. Excavation into the hard caliche unit may be completed at near-vertical. No heavy equipment should be allowed near the top of temporary cut slopes unless the cut slopes are adequately braced. Final (permanent) fill slopes should be graded to an angle of 2H:1V or flatter. Where unstable soils are encountered, flatter slopes may be required.

The presence of the noted relatively shallow cemented gravel stratum at the site poses a challenge/difficulty for excavation with traditional earthwork equipment. Appropriately capable rippers and/or excavator-mounted hoe-rams may be required for excavation into/through this layer.

14.5 Utility Excavation, Pipe Bedding and Trench Backfill

To provide suitable support and bedding for the pipe, we recommend the utilities be founded on suitable bedding material consisting of clean sand and/or sand & gravel mixture. To minimize trench subgrade disturbance during excavation, the excavator should use a smooth-edged bucket rather than a toothed bucket.

Pipe bedding and pipe zone materials shall conform to Section 9-03.12(3), Gravel Backfill for Pipe Zone Bedding, of the Washington State Department of Transportation (WSDOT) 2018 Standard Specifications. Pipe bedding should provide a firm uniform cradle for support of the pipes. A minimum 4-inch thickness of bedding material beneath the pipe should be provided. Prior to installation of the pipe, the pipe bedding should be shaped to fit the lower part of the pipe exterior with reasonable closeness to provide uniform support along the pipe. Pipe bedding material should be used as pipe zone backfill and placed in layers and tamped around the pipes to obtain complete contact. To protect the pipe, bedding material should extend at least 6 inches above the top of pipe.

Placement of bedding material is particularly critical where maintenance of precise grades is essential. Backfill placed within the first 12 inches above utility lines should be compacted to at least 90% of the maximum dry density (ASTM D1557), such that the utility lines are not damaged during backfill placement and compaction. In addition, rock fragments greater than 1 inch in maximum dimension should be excluded from this first lift. The remainder of the utility excavations should be backfilled and compacted to 95% of the maximum dry density as determined by ASTM D1557.

Onsite soils are considered suitable for utility trench backfill provided they are free of oversize material and can be adequately compacted. All excavations should be wide enough to allow for compaction around the haunches of pipes and underground tanks. We recommend that utility trenching, installation, and backfilling conform to all applicable federal, state, and local regulations such as OSHA and WISHA for open excavations.

Compaction of backfill material should be accomplished with soils within $\pm 2\%$ of their optimum moisture content in order to achieve the minimum specified compaction levels recommended in this report. However, initial lift thickness could be increased to levels recommended by the manufacturer to protect utilities from damage by compacting equipment.

14.6 Imported Crushed Rock Structural Fill

Where and as needed, imported structural fill shall consist of well-graded, crushed aggregate material meeting the grading requirements of WSDOT 2018 Standard Specifications, Section 9-03.9(3) (1-1/4 inch minus Base Course Material) presented here:

Table 4: WSDOT Standard Spec. 9-03.9(3)

| Sieve Size | Percent Passing (by Weight) |
|-------------------|------------------------------------|
| 1¼ Inch Square | 99 - 100 |
| 1 Inch Square | 80 - 100 |
| 5/8 Inch Square | 50 – 80 |
| U.S. No. 4 | 25 - 45 |
| U.S. No. 40 | 3 – 18 |
| U.S. No. 200 | Less than 7.5 |

A fifty (50) pound sample of each imported fill material shall be collected by GNN personnel prior to placement to ensure proper gradation and establish the moisture-density relationship (proctor curve).

14.7 Compaction Requirements for Engineered Fill

All fill or backfill shall be approved by a representative of the GER, placed in uniform lifts, and compacted to a minimum 95% of the maximum dry density as determined by ASTM D1557. The compaction effort must be verified by a representative of the GER in the field using a nuclear density gauge in accordance with ASTM D6938. The thickness of the loose, non-compacted lift of fill shall not exceed 8 inches for heavy-duty compactors or 4 inches for hand operated compactors.

14.8 O&M Building Foundation Bearing Support

The proposed O&M building may be supported on conventional shallow foundations in accordance with the recommendations of this report. The minimum footing depth shall be 24 inches below adjacent grades for frost protection and bearing capacity considerations. All foundations shall be constructed to bear directly on the caliche layer or on 1¼-minus crushed rock structural fill extending down to the caliche layer. Foundation excavations shall be cleared of all loose soils and shall be observed by a representative of the GER to confirm the dense caliche has been exposed. Footings constructed in accordance with the above recommendations may be designed for an allowable bearing capacity of **2,500 pounds per square foot (psf)**. The allowable bearing pressure may be increased by 1/3 for short-term transient loading conditions. The estimated total settlement for footings is approximately 1-inch with differential settlement less than half that magnitude. The weight of the foundation concrete below grade may be neglected in dead load computations.

Lateral forces on foundations from short term wind and seismic loading would be resisted by friction at the base of foundations and passive earth pressure against the buried portions. We

recommend an allowable passive earth pressure for the compacted onsite soil of **200 pcf**. This lateral foundation resistance value includes a factor of safety of 1.5. We recommend a coefficient of friction of **0.40** be used between cast-in-place concrete and native caliche. An appropriate factor of safety should be used to calculate sliding resistance at the base of footings.

14.9 O&M Building Slab-on-Grade Floors

Place a minimum 6-inch layer of crushed aggregate fill beneath the slabs. The material shall meet the WSDOT 2018 Standards Specifications, Section 9-03.9(3), “Crushed Surfacing Top Course”, with less than 5 percent passing the No. 200 sieve (fines). The crushed rock material shall be compacted to at least 95% of the maximum dry density as determined by the ASTM D1557 method. Prior to placing the crushed rock layer, the native subgrade shall be moisture-conditioned and compacted to minimum 95% of the maximum dry density as determined by ASTM D1557 to a minimum depth of 12 inches. Any soft spots or areas displaying pumping/deformation during compaction shall be over-excavated an additional 12 inches, backfilled with imported granular structural fill and re-compacted.

We recommend a modulus of subgrade reaction equal to **120 pounds per cubic inch (pci)** based on a value for gravel presented in the Portland Cement Association publication No. EB075.01D. Slab thickness, reinforcement and joint spacing shall be determined by a licensed engineer based on the intended use and loading.

14.10 Driven Posts Pile Foundation

We understand that the PV array structures will be supported on driven posts pile foundations. The selection of pile type, size, and method of installation shall be determined by the design-build racking contractor considering the geotechnical parameters presented in this report. Uplift and overturning resistance shall be factored into the foundation design.

The structural designer shall determine the pile length based on the structural demands for axial compressive loads, lateral loads and overturning moments. Pile foundations in cemented/hardpan soils units shall be socketed to a sufficient depth to satisfy structural demands to resist uplift and lateral loads and shall fulfill minimum penetration and length requirements. Foundation supported on bedrock shall penetrate a minimum 6 inches into the weathered basalt bedrock unit. Additional

penetration into the dense bearing stratum may be required to compensate for the skin friction lost due to surface disturbance caused by installation.

Axial capacity of driven piles may be estimated based on the perimeter of the pile and embedment depth. End bearing of driven piles should be neglected. For pipe piles the perimeter is the circumference, for wide flange beams, the perimeter is twice the sum of the flange width and web depth. We recommend the upper 24 inches of soil for each pile be neglected for capacity; however, the upper 18 inches may be included for overburden pressure.

Based on the findings of our subsurface investigation, we recommend that post pile foundations be supported on the underlying hardpan/bedrock unit. If design requires pile lengths to be greater 8 to 9 feet, pre-drilling of the hardpan/bedrock may be warranted.

An allowable end bearing pressure of **4,000 psf** may be used for the design of driven post/pile foundations bearing directly on the underlying hardpan/bedrock unit. This value may be increased one-third (33%) for short-term (transient) loading events.

We estimate the total settlement for piles constructed per the recommendations of this report to be less than 1-inch, with differential settlement less than half that magnitude.

Lateral forces on foundation from short term wind and seismic loading would be resisted by friction at the base of piles and passive earth pressure against the buried portions. We recommend an allowable passive earth pressure within the upper silty soils of **140 pcf and 250 pcf** for the underlying cemented soil units. This lateral foundation resistance value includes a factor of safety of 1.5. We recommend an allowable coefficient of skin friction between steel pile (assumed) and the loose native silt of **0.15**. We recommend a coefficient of skin friction of **0.35** be used between steel pile (assumed) and the underlying hardpan layer. An appropriate factor of safety should be used to calculate sliding resistance at the base of the pile. The following table provides additional geotechnical parameters for use in design:

Table 5: Geotechnical Design Parameters

| Soil Type | Soil Angle of Friction | Effective Unit Weight | Apparent Cohesion | p-y modulus, k |
|--------------------------------------|-------------------------------|------------------------------|--------------------------|-----------------------|
| Loose Silt with Sand | 26 degrees | 80 pcf | <i>ignore</i> | 25 pci |
| Caliche/Hardpan/Silt stone/Sandstone | 32 degrees | 105 pcf | 200 psf | 300 pci |
| Weathered Basaltic Bedrock | 40 degrees | 145 pcf | 400 psf | 500 pci |

Driven Pile Foundation Installation Considerations

If refusal is encountered during installation, the vibration action of the hammer could result in an oversized installation hole that greatly reduces axial and lateral capacity of the installed pile. If pile refusal occurs, we recommend the pile be immediately smoothly withdrawn and to predrill the installation location. The pre-drilled hole should have a diameter of at least one (1) inch smaller than the pipe pile outer diameter (O.D.) or two (2) inches smaller than the diagonal dimension of a wide flange beam. Test driving of pile should be considered to determine the proper pre-drill hole size.

A representative of the GNN should observe the driven pile installation and materials penetrated to confirm that the conditions encountered are consistent with those used in our analyses and to evaluate conditions that may affect pile capacities. We recommend that pile load testing shall be conducted before installation of production piles for this project. The pile load test shall be monitored by a geotechnical representative of GNN and the results reviewed by the GER.

14.11 Drilled & Grouted Posts Pile Foundation

Due to the presence of shallow cemented gravels that may likely prevent driven pile advancement, the PV array structures may be supported on drilled and grouted posts pile foundations

14.12 Foundation Options for Substation Equipment Pads

Based on subsurface conditions encountered at the site, we believe that shallow spread footings and/or mat foundations may both be suitable options for foundation types for the proposed substation located southeast of the intersection of Morris Lane and Den Beste Road.

Spread Footings: Structures supported on conventional spread footings shall be founded on crushed rock structural fill overlying compacted native soils. All footings should be placed at least

24 inches below exterior finished grade for frost protection. We recommend at least 12-inches of 1½" minus crushed rock fill be placed directly beneath the footing base in two lifts, with each lift compacted to at least 95% of the maximum dry density as determined by ASTM D1557. The lateral extent of crushed rock shall be 12 inches on all sides of the foundation. Prior to placing the structural gravel fill material, the native subgrade soil shall be scarified to a minimum depth of 12-inch, moisture conditioned to near optimum and compacted to at least 95% of the maximum dry density as determined by ASTM D1557. Spread footings supported on compacted structural gravel fill can be proportioned for a maximum allowable bearing pressure of **2,000 psf**.

This allowable bearing pressure include a factor of safety of 3. Allowable bearing pressure may be increased by one-third (33%) for seismic loading conditions. In our opinion, foundations constructed on compacted structural gravel fill overlying compacted native subgrade will settle less than 1-inch, with differential settlement less than half that magnitude.

Mat Foundations: Mat foundations shall be supported on a minimum 12-inches of 1½" minus crushed rock fill be placed directly beneath the mat in two lifts, with each lift compacted to at least 95% of the maximum dry density as determined by ASTM D1557. Prior to placing the structural gravel fill material, the native subgrade soil shall be scarified to a minimum depth of 12-inch, moisture conditioned (as necessary) and re-compacted to at least 95% of the maximum dry density as determined by ASTM D1557. The lateral extent of crushed rock shall be 12 inches on all sides of the foundation. A modulus of subgrade reaction of **200 pci** may considered for mat foundations supported on minimum 18-inches of imported crushed rock on prepared and compacted subgrade.

For design purposes, an allowable passive earth pressure of 220 pcf and 300 pcf (equivalent fluid unit weight) is appropriate for compacted onsite backfill and crushed rock structural fill, respectively. This lateral foundation resistance value includes a factor of safety of 1.5. A coefficient of base friction of 0.45 (mass concrete poured directly over granular structural fill) may be used for the frictional resistance against sliding. An appropriate factor of safety shall be used to calculate sliding resistance at the base of footings.

Based on the findings of our exploration, our experience with similar soils, and the results of our laboratory testing, effect of frost heave and soil expansion are considered negligible.

14.13 Subgrade Protection

The degree to which construction grading problems develop is expected to be dependent, in part, on the time of year that construction proceeds and the precautions which are taken by the contractor to protect the subgrade. The near-surface fine-grained soils currently present on site are considered to be moisture and disturbance sensitive due to their fines content and may become unstable (pumping) if allowed to increase in moisture content and are disturbed (rutted) by construction traffic if wet. If necessary, the construction access road should be covered with a layer of gravel or quarry spalls course. The soils are also susceptible to erosion in the presence of moving water. The soils shall be stabilized to minimize the potential of erosion into the foundation excavation. The site shall be graded to prevent water from ponding within construction areas and/or flowing into excavations. Accumulated water must be removed immediately along with any unstable soil. Foundation concrete shall be placed and excavations backfilled as soon as possible to protect the bearing grade. We further recommend that soils that become unstable are to be either:

- Removed and replaced with structural compacted gravel fill, or
- Mechanically stabilized with a coarse crushed aggregate (possibly underlain with a geotextile) and compacted into the subgrade.

14.14 Surface Drainage

With respect to surface water drainage, we recommend that the ground surface be sloped to drain away from the structure. Final exterior site grades shall promote free and positive drainage from the building areas. Water shall not be allowed to pond or to collect adjacent to foundations or within the immediate building area. We recommend that a gradient of at least 5% for a minimum distance of 10 feet from the building perimeter be provided, except in paved locations. In paved areas, a minimum gradient of 1% should be provided unless provisions are included for collection/disposal of surface water adjacent to the structure. Catch basins, drainage swales, or other drainage facilities should be aptly located. All surface water such as that coming from roof downspouts and catch basins be collected in tight drain lines and carried to a suitable discharge point. Surface water and downspout water should not discharge into a perforated or slotted subdrain, nor should such water discharge onto the ground surface adjacent to the building. Cleanouts should be provided at convenient locations along all drain lines.

14.15 Wet Weather Conditions

The onsite fine-grained soils (Silt/Loess) are moisture sensitive during handling and compaction. Proceeding with earthwork using these soils during wet weather could add significant project costs and/or delays. The stability of exposed soils may rapidly deteriorate due to a change in moisture content. Therefore, if at all possible, complete site clearing, preparation, and earthwork during periods of warm, dry weather when soil moisture can be controlled by aeration. During or subsequent to wet weather, drying or compacting the on-site soils will be difficult. It will be necessary to either amend the on-site soils or import granular materials for use as structural fill. If earthwork takes place in wet weather or wet conditions, the following recommendations should be followed:

- Fill materials should consist of imported clean, granular soil, with less than 3 percent fines (passing the No. 200 sieve size), based on wet-sieving the soil fraction passing the ¾-inch sieve.
- Earthwork should be accomplished in small sections and carried through to completion to reduce exposure to wet weather. Soils that becomes too wet for compaction should be removed and replaced with clean, granular material.
- The construction area ground surface should be sloped and sealed to reduce water infiltration, to promote rapid runoff, and to prevent water ponding.
- To prevent soil disturbance, the size or type of equipment may have to be limited.
- Carefully stage equipment and/or stockpiles, route construction equipment away from subgrades, and implement aggressive site drainage procedures to help reduce saturating subgrades during wet weather conditions.
- Equipment with large tracks, lugs, or having toothed buckets has a significant potential to disturb the site soil prior to or following compaction. Rubber-tired vehicles should not access prepared subgrades unless the subgrade is sufficiently stiff to allow construction traffic without disturbance.
- Maintain the subgrade in a compacted condition and protect subgrades from construction traffic disturbance after they have been prepared and meet compaction requirements. Consequently, do not operate construction equipment or vehicles on prepared subgrade areas during wet weather conditions.

- Prior to rain and other events that may cause fine-grained soil (silt and silty sand) to exceed optimum moisture content, stabilize such soils to minimize potential for erosion into adjacent excavations.
- Earthwork should not be performed immediately after rainfall, or until soil can dry sufficiently to allow construction traffic without disturbing the subgrade. After inclement weather, inspect all subgrade areas prepared before the inclement weather conditions.
- For soils exhibiting pumping, rutting, weaving, or otherwise exhibiting unstable performance, moisture-condition (typically dry) and re-compact the soil to structural fill requirements, or remove and replace the unstable soils with imported free draining granular fill material acceptable to the GER
- Work areas and stockpiles should be covered with plastic. Straw bales, straw wattles, geotextile silt fences, and/or other measures should be used as appropriate to control soil erosion.
- Excavation and structural fill placement should be observed on a full-time basis by a representative of our geotechnical engineer to determine that unsuitable materials are fully removed and that suitable compaction and site drainage is achieved.

14.16 Slope Maintenance and Erosion Protection

Proper slope protection and maintenance will help minimize slope erosion and improve the stability of the project slopes. The project soils are prone to erosion and will require appropriate BMP protection and maintenance. Positive drainage should be provided at the tops of all slopes to divert runoff away from the face. Swales constructed in native soils should be lined with suitable no-erosive material. Erosion protection should be provided, especially where concentrated runoff is anticipated.

The need for and design of flood control and erosion protection measures is within the purview of the design civil engineer. In general, erosion should be mitigated with best management practices (BMPs) consisting of proper drainage design including collecting and disposal (conveyance) of water to approved points of discharge in a non-erosive manner. Appropriate project design, construction, and maintenance will be necessary to mitigate the site erosion concerns.

15.0 CONTINUING GEOTECHNICAL SERVICES

GNN recommends that the Client should maintain an adequate program of geotechnical consultation, construction monitoring, and soils testing during the final design and construction phases to monitor compliance with GNN's geotechnical recommendations. Maintaining GNN as the geotechnical consultant from beginning to end of the project will provide continuity of services. If GN Northern, Inc. is not retained by the owner/developer and/or the contractor to provide the recommended geotechnical inspections/observations and testing services, the geotechnical engineering firm or testing/inspection firm providing tests and observations shall assume the role and responsibilities of Geotechnical Engineer-of-Record.

GNN can provide construction monitoring and testing as additional services. The costs of these services are not included in our present fee arrangement, but can be obtained from our office. The recommended construction monitoring and testing includes, but is not necessarily limited to, the following:

- Consultation during the design stages of the project.
- Review of the grading and drainage plans to monitor compliance and proper implementation of the recommendations in GNN's Report.
- Observation and quality control testing during site preparation, grading, and placement of engineered fill as required by the local building ordinances.
- Geotechnical engineering consultation as needed during construction

16.0 LIMITATIONS OF THE GEOTECHNICAL SITE INVESTIGATION REPORT

This GEOTECHNICAL SITE INVESTIGATION REPORT (“Report”) was prepared for the exclusive use of the Client. GN Northern, Inc.’s (GNN) findings, conclusions and recommendations in this Report are based on a limited number of widely spaced points of subsurface exploration across the project site, and GNN’s understanding of the proposed project at the time the Report is prepared. Furthermore, GNN’s findings and recommendations are based on the assumption that soil, rock and/or groundwater conditions do not vary significantly from those found at specific exploratory locations at the project site. Due to the large nature of the site, variations in soil, bedrock and/or groundwater conditions could exist between and beyond the areas observed and explored. The nature and extent of these variations may not become evident until during or after construction. Variations in soil, bedrock and groundwater may require additional studies, consultation, and revisions to GNN’s recommendations in the Report.

In many cases the scope of geotechnical exploration and the test locations are selected by others without consultation from the geotechnical engineer/consultant. GNN assumes no responsibility and, by preparing this Report, does not impliedly or expressly validate the scope of exploration and the test locations selected by others.

This Report’s findings are valid as of the issued date of this Report. However, changes in conditions of the subject property or adjoining properties can occur due to passage of time, natural processes, or works of man. In addition, applicable building standards/codes may change over time. Accordingly, findings, conclusions, and recommendations of this Report may be invalidated, wholly or partially, by changes outside of GNN’s control. Therefore, this Report is subject to review and shall not be relied upon after a period of **three (3) year** from the issued date of the Report.

In the event that any changes in the nature, design, or location of structures are planned, the findings, conclusions and recommendations contained in this Report shall not be considered valid unless the changes are reviewed by GNN and the findings, conclusions, and recommendations of this Report are modified or verified in writing.

This Report is issued with the understanding that the owner or the owner’s representative has the responsibility to bring the findings, conclusions, and recommendations contained herein to the

attention of the architect and design professional(s) for the project so that they are incorporated into the plans and construction specifications, and any follow-up addendum for the project. The owner or the owner's representative also has the responsibility to verify that the general contractor and all subcontractors follow such recommendations during construction. It is further understood that the owner or the owner's representative is responsible for submittal of this Report to the appropriate governing agencies. The foregoing notwithstanding, no party other than the Client shall have any right to rely on this Report and GNN shall have no liability to any third party who claims injury due to reliance upon this Report, which is prepared exclusively for Client's use and reliance.

GNN has provided geotechnical services in accordance with generally accepted geotechnical engineering practices in this locality at this time. GNN expressly disclaims all warranties and guarantees, express or implied.

Client shall provide GNN an opportunity to review the final design and specifications so that earthwork, drainage and foundation recommendations may be properly interpreted and implemented in the design and specifications. If GNN is not accorded the review opportunity, GNN shall have no responsibility for misinterpretation of GNN's recommendations.

Although GNN can provide environmental assessment and investigation services for an additional cost, the current scope of GNN's services does not include an environmental assessment or an investigation for the presence or absence of wetlands, hazardous or toxic materials in the soil, surface water, groundwater, or air on, below, or adjacent to the subject property.

APPENDICES

Appendix I

Vicinity Map (Figure 1)

Site Exploration Maps (Figures 2 & 3)

Fault & Geologic Map (Figure 4)

Liquefaction Susceptibility Map (Figure 5)





FIGURE 1: VICINITY MAP

PROJECT NO. 220-1274






FIGURE 2: SITE EXPLORATION MAP








FIGURE 5: LIQUEFACTION SUSCEPTIBILITY MAP

PROJECT

GOOSE PRAIRIE

ADDRESS

11900-12898 WA -24
MOXEE, WA 98936

DRAWING

TITLE:
CONCEPT LAYOUT
SHEET NUMBER:

A-001

SCALE:

1" = 400'

DRAWN BY:

CG

CHECKED BY:

DATE:

10/28/2020

REVISIONS:

DESCRIPTION



THIS FACILITY CONSISTS OF THE DESIGN AND INSTALLATION OF AN 80.00MWac SOLAR PHOTOVOLTAIC + BATTERY SYSTEM. MODULES ARE TO BE MOUNTED IN SINGLE AXIS TRACKERS, WHICH FOLLOW THE SUN FROM EAST TO WEST THROUGHOUT THE DAY. INTERCONNECTION TO BE COORDINATED WITH THE LOCAL UTILITY.

LEGEND

- GRAVEL ACCESS ROAD
- FACILITY STAGING / PARKING AREA
- FACILITY O&M BUILDING
- FACILITY SUBSTATION
- PARCEL BOUNDARY
- PARCEL ZONING OFFSET
- NEIGHBOR PARCEL BOUNDARY
- FACILITY AREA EXTENT
- FACILITY SECURITY FENCE
- EXISTING UTILITY LINE
- GENERATION TIE LINE
- EXISTING UTILITY RISER
- PROPOSED NEW RISER



WRITTEN DIMENSIONS ON THIS PLAN SHALL SUPERCEDE SCALED DIMENSIONS. CONTRACTORS ARE RESPONSIBLE FOR FIELD VERIFYING ALL DIMENSIONS. THIS DRAWING, DESIGN, CONCEPT AND ARRANGEMENT REMAIN THE PROPERTY OF ONEENERGY RENEWABLES AND SHALL NOT BE COPIED, DISCLOSED OR REPRODUCED WITHOUT CONSENT.



YAKIMA COUNTY VICINITY MAP

SITE DETAILS:

| | |
|------------------|--------------------------------|
| SITE LAT: | 46.528557° |
| SITE LONG: | -120.240075° |
| PARCEL ID: | 21121811003 |
| OWNER: | ESTATE OF WILLMAE G MEACHAM |
| ACREAGE: | 467.90 |
| EXISTING ZONING: | AG |
| EXISTING USE: | 83 CURRENT USE AGRICULTURE |
| PARCEL ID: | 21121843004 |
| OWNER: | ESTATE OF WILLMAE G MEACHAM |
| ACREAGE: | 18.74 |
| EXISTING ZONING: | AG |
| EXISTING USE: | 83 CURRENT USE AGRICULTURE |
| PARCEL ID: | 21121844003 |
| OWNER: | ESTATE OF WILLMAE G MEACHAM |
| ACREAGE: | 32.50 |
| EXISTING ZONING: | AG |
| EXISTING USE: | 83 CURRENT USE AGRICULTURE |
| PARCEL ID: | 21120721001 |
| OWNER: | S MARTINEZ LIVESTOCK INC |
| ACREAGE: | 291.34 |
| EXISTING ZONING: | AG |
| EXISTING USE: | 83 CURRENT USE AGRICULTURE |
| PARCEL ID: | 21120711001 |
| OWNER: | S MARTINEZ LIVESTOCK INC |
| ACREAGE: | 327.9 |
| EXISTING ZONING: | AG |
| EXISTING USE: | 83 CURRENT USE AGRICULTURE |
| PARCEL ID: | 21120832001 |
| OWNER: | S MARTINEZ LIVESTOCK INC |
| ACREAGE: | 79.52 |
| EXISTING ZONING: | AG |
| EXISTING USE: | 81 AGRICULTURE NOT CURRENT USE |
| PARCEL ID: | 21120811001 |
| OWNER: | S MARTINEZ LIVESTOCK INC |
| ACREAGE: | 269.68 |
| EXISTING ZONING: | AG |
| EXISTING USE: | 83 CURRENT USE AGRICULTURE |
| PARCEL ID: | 21121721002 |
| OWNER: | S MARTINEZ LIVESTOCK INC |
| ACREAGE: | 80.29 |
| EXISTING ZONING: | AG |
| EXISTING USE: | 83 CURRENT USE AGRICULTURE |

DESIGN SUMMARY:

| | |
|----------------------|---------------------------|
| MODULE POWER: | 445W |
| MODULE COUNT: | 260,550 |
| ARRAY DC VOLTAGE: | 1500V |
| SOLAR INVERTER SIZE: | 2,105MW/2,500MVA @50C |
| SOLAR INVERTER QTY: | 38 +/- |
| DC CAPACITY: | 115.94MMWdc @ STC (Front) |
| AC CAPACITY: | 80,000MWac |
| DC/AC RATIO: | 1.45 |
| GROUND COVER RATIO: | 33.25% |
| GROUND SNOW LOAD: | 15 PSF |
| ASCE 7-10 WINDSPEED: | 110 MPH |

LAND USE SUMMARY:

| | |
|------------------------|---------------|
| TOTAL PARCEL AREA: | 1567.87 ACRES |
| FACILITY AREA EXTENT: | 791.39 ACRES |
| TOTAL FENCED AREA: | 590.00 ACRES |
| TOTAL ACCESS ROAD: | 23.09 ACRES |
| FACILITY STAGING AREA: | 2.12 ACRES |
| O&M FACILITY AREA: | 0.171 ACRES |
| FACILITY SUBSTATION: | 0.556 ACRES |

KEY NOTES:

- PRELIMINARY LOCATION OF LINE TAP. FINAL LOCATION IS SUBJECT TO CHANGE BASED ON BPA INTERCONNECTION ENGINEERING STUDY RESULTS.
- MEDIUM VOLTAGE LINE TO CONNECT NORTHERN PROJECT AREA TO FACILITY SUBSTATION. EXACT LOCATION TO BE DETERMINED.
- FACILITY SHALL MAINTAIN A MINIMUM 60' SETBACK FROM ALL WATERWAYS.

GENERAL NOTES:

- PARCEL BOUNDARIES PROVIDED BY YAKIMA COUNTY, WA OPEN DATA PORTAL.
- NO FEDERAL EMERGENCY MANAGEMENT AGENCY (FEMA) FLOOD HAZARD ZONES ARE FOUND ON THE PARCEL ON WHICH THE FACILITY IS PROPOSED.
- NATIONAL WETLAND INVENTORY (NWI) WETLANDS SHOWN. ALL ELECTRICAL EQUIPMENT MINIMUM OF 50' FROM HIGH WATER LINE. NWI WETLANDS WILL BE GROUND-TRUTHED VIA A PROFESSIONAL WETLAND SURVEY AND DELINEATION SITE LAYOUT WILL ADJUST ACCORDING TO RESULTS.
- LOCATION OF WASHINGTON WATERCOURSES PROVIDED BY WASHINGTON GEOSPATIAL OPEN DATA PORTAL.
- FACILITY FALLS WITHIN A MILITARY TRAINING ROUTE BUFFER. CONSULTATION WITH DEPARTMENT OF DEFENSE HAS BEGUN. NO CONCERNS FLAGGED BY DEPARTMENT OF DEFENSE.
- FACILITY LAYOUT INCLUDES AN OPTIONAL BATTERY STORAGE SYSTEM CAPABLE OF SERVING AS 80MW OF LOAD OR GENERATION. APPLICANT SEEKS FLEXIBILITY BETWEEN AN AC-COUPLED OR DC-COUPLED SYSTEM. BOTH ARE SHOWN FOR ILLUSTRATIVE PURPOSES.
- PROPOSED FACILITY ACCESS POINT TO BE COORDINATED WITH WASHINGTON DEPARTMENT OF TRANSPORTATION AND YAKIMA COUNTY TRANSPORTATION SERVICES DIVISION.
- THE FACILITY WILL COMPLY WITH ALL ZONING AND COUNTY REQUIREMENTS.
- LOCATION OF ALL PROPOSED EQUIPMENT ARE SUBJECT TO CHANGE. CHANGES TO SITE PLAN ARE TO STAY WITHIN THE FACILITY AREA EXTENT AS SHOWN.
- COLLECTION LINE LOCATIONS ARE PENDING BASED ON FURTHER ENGINEERING ANALYSIS.
- PROJECT IS IN YAKIMA COUNTY FIRE DISTRICT #4 AND WILL COMPLY WITH ALL REQUIREMENTS OF THE FIRE OFFICIAL. ACCESS ROADS AND GATES WILL COMPLY WITH THE APPLICABLE VERSION OF THE INTERNATIONAL FIRE CODE AS ADOPTED BY THE STATE OF WASHINGTON. GATES 20' IN WIDTH WITH ACCESSIBLE HARDWARE PER FIRE DEPARTMENT REQUIREMENTS SHALL BE INSTALLED. FIRE ACCESS ROADS SHALL BE 20' IN WIDTH, WITH INNER TURNING RADIUS OF 30' AND OUTER TURNING RADIUS OF 45'.
- THE AMENDED 2018 INTERNATIONAL FIRE CODE WILL REPLACE THE 2015 CODE EFFECTIVE JULY 1, 2020.
- THIS SITE CONSISTS OF TWO NRCS SOIL TYPES: WILLIS SILT LOAM AND MOXEE SILT LOAM.
- REFER TO STUDY RESULTS PERFORMED BY WEST INC. FOR DETAILED INFORMATION REGARDING THREATENED, ENDANGERED AND SENSITIVE SPECIES FOUND ON SITE.

GOOSE PRAIRIE SOLAR + STORAGE 80.00MWAC - CONCEPTUAL LAYOUT

SCALE: 1" = 400'

Appendix II
Exploratory Boring & Test Pit Logs
Key Chart (for Soil Classification)



GN Northern, Inc.
722 N. 16th Avenue Suite 31
Yakima, Washington 98902
Telephone: (509) 248-9798
Fax: (509) 248-4220

BORING NUMBER B-1

PAGE 1 OF 1

CLIENT OER WA Solar 1, LLC

PROJECT NAME Goose Prairie Photovoltaic (PV) Solar Array Project

PROJECT NUMBER 220-1274

PROJECT LOCATION Near Moxee, Yakima County Washington

DATE STARTED 9/15/20

COMPLETED 9/15/20

GROUND ELEVATION 1552 ft

HOLE SIZE 6 inches

DRILLING CONTRACTOR Western States Soil Conservation, Inc.

GROUND WATER LEVELS:

DRILLING METHOD CME 55 Track-Mounted Rig

AT TIME OF DRILLING ---

LOGGED BY KAH

CHECKED BY IM

AT END OF DRILLING ---

NOTES Approx. GPS Coords.: 46°32'4.27"N, 120°13'49.68"W

AFTER DRILLING ---

GENERAL BH / TP / WELL - GINT STD US LAB.GDT - 10/12/20 10:41 - C:\USERS\YONG LEE\DROPBOX\ACTIVE PROJECTS\220-1274 ONEENERGY - GOOSE PRAIRIE SOLAR ARRAY; NEAR MOXEE WA\220-1274 LOGS.GPJ

| DEPTH (ft) | SAMPLE TYPE NUMBER | BLOW COUNTS (N VALUE) | U.S.C.S. | GRAPHIC LOG | MATERIAL DESCRIPTION |
|---|-----------------------|-----------------------------|----------|----------------|---|
| 0 | | | | | |
| | | | GM | | SILTY GRAVEL WITH SAND, (GM) tan to pink, dry, very dense, some cobbles |
| | ▲ SPT | 30-50/5" | | | |
| 5 | | | | | |
| | ▲ SPT | 7-15-23 (38) | | | |
| | ▲ SPT | 50/4" | | | |
| 10 | | | | | |
| | ▲ SPT | 38-50/2" | | | |
| 15 | | | SM | | |
| | ▲ SPT | 7-19-43 (62) | | | |
| 20 | | | | | |
| | ▲ SPT | 50/4" | | | |
| 25 | | | | | |
| | ▲ SPT | 50-50/2" | | | |
| 30 | | | | | |
| | ▲ SPT | 18-25-48 (73) | | | |
| 35 | | | | | |
| | ▲ SPT | 50/3" | | | |
| 40 | | | | | |
| | ▲ SPT | 50/5" | | | |
| - Groundwater not encountered at time of drilling - Referenced elevations are approximate and based on Google Earth topography Bottom of borehole at 40.4 feet. | | | | | |



GN Northern, Inc.
722 N. 16th Avenue Suite 31
Yakima, Washington 98902
Telephone: (509) 248-9798
Fax: (509) 248-4220

BORING NUMBER B-2

PAGE 1 OF 1

CLIENT OER WA Solar 1, LLC

PROJECT NAME Goose Prairie Photovoltaic (PV) Solar Array Project

PROJECT NUMBER 220-1274

PROJECT LOCATION Near Moxee, Yakima County Washington

DATE STARTED 9/16/20

COMPLETED 9/16/20

GROUND ELEVATION 1546 ft

HOLE SIZE 6 inches

DRILLING CONTRACTOR Western States Soil Conservation, Inc.

GROUND WATER LEVELS:

DRILLING METHOD CME 55 Track-Mounted Rig

AT TIME OF DRILLING ---

LOGGED BY KAH

CHECKED BY IM

AT END OF DRILLING ---

NOTES Approx. GPS Coords.: 46°32'4.30"N, 120°13'52.78"W

AFTER DRILLING ---

GENERAL BH / TP / WELL - GINT STD US LAB.GDT - 10/12/20 10:41 - C:\USERS\YONG LEE\DROPBOX\ACTIVE PROJECTS\220-1274 ONEENERGY - GOOSE PRAIRIE SOLAR ARRAY - NEAR MOXEE WA\220-1274 LOGS.GPJ

| DEPTH (ft) | SAMPLE TYPE NUMBER | BLOW COUNTS (N VALUE) | TESTS | U.S.C.S. | GRAPHIC LOG | MATERIAL DESCRIPTION |
|---------------|-----------------------|-----------------------------|------------------------|----------|----------------|---|
| 0 | | | | | | |
| 5 | SPT | 50/5" | | GM | | SILTY GRAVEL WITH SAND, (GM) tan to pink, dry, dense, ashy, with cobbles |
| | SPT | 50 | | | | |
| | SPT | 50/3" | | | | |
| 10 | SPT | 50/3" | | SM | | SILTY SAND, (SM) brown, fine to coarse grained, damp, very dense, trace gravel |
| 15 | SPT | 17-36-50/3" | MC = 6% Fines = 77% | | | - becomes damp to moist, fine grained, with Silt with Sand (ML) |
| 20 | SPT | 7-14-50/6" | | ML | | SILT WITH SAND (ML) / SANDY SILT, (ML) brown, moist, very dense, (siltstone) [Ellensburg Formation] |
| 25 | SPT | 30-42-50/2" | | | | |
| 30 | SPT | 17-30-47 (77) | | SM | | SILTY SAND, (SM) fine grained, moist, very dense, (sandstone) |
| 35 | SPT | 18-34-50/4" | | | | - some gravel - some Sandy Silt (ML) |
| 40 | SPT | 17-34-50/3" | | | | - trace gravel - with gravel |
| 41.3 | | | | | | |

- Groundwater not encountered at time of drilling
- Referenced elevations are approximate and based on Google Earth topography

Bottom of borehole at 41.3 feet.



GN Northern, Inc.
722 N. 16th Avenue Suite 31
Yakima, Washington 98902
Telephone: (509) 248-9798
Fax: (509) 248-4220

BORING NUMBER B-3

PAGE 1 OF 1

CLIENT OER WA Solar 1, LLC

PROJECT NAME Goose Prairie Photovoltaic (PV) Solar Array Project

PROJECT NUMBER 220-1274

PROJECT LOCATION Near Moxee, Yakima County Washington

DATE STARTED 9/16/20

COMPLETED 9/16/20

GROUND ELEVATION 1550 ft

HOLE SIZE 6 inches

DRILLING CONTRACTOR Western States Soil Conservation, Inc.

GROUND WATER LEVELS:

DRILLING METHOD CME 55 Track-Mounted Rig

AT TIME OF DRILLING ---

LOGGED BY KAH

CHECKED BY IM


AT END OF DRILLING ---

NOTES Approx. GPS Coords.: 46°32'2.95"N, 120°13'51.13"W

AFTER DRILLING ---

GENERAL BH / TP / WELL - GINT STD US LAB.GDT - 10/12/20 10:41 - C:\USERS\YONG LEE\DROPBOX\ACTIVE PROJECTS\220-1274 ONEENERGY - GOOSE PRAIRIE SOLAR ARRAY; NEAR MOXEE WA\220-1274 LOGS.GPJ

| DEPTH (ft) | SAMPLE TYPE NUMBER | BLOW COUNTS (N VALUE) | U.S.C.S. | GRAPHIC LOG | MATERIAL DESCRIPTION |
|---------------|-----------------------|-----------------------------|----------|----------------|---|
| 0 | | | | | |
| 5 | SPT | 12-50/2" | GM | | SILTY GRAVEL WITH SAND, (GM) tan, dry, dense, ashy |
| | SPT | 50/5" | | | |
| 10 | SPT | 13-44-50/3" | ML | | SANDY SILT, (ML) brown, damp, very dense, (siltstone) [Ellensburg Formation] |
| | SPT | 12-29-39 (68) | | | |
| 15 | SPT | 40-38-30 (68) | | | |
| 20 | SPT | 16-36-50/5" | | | - becomes damp to moist, fine grained |
| 25 | SPT | 27-50/4" | | | - trace gravel |
| 30 | SPT | 27-50/5" | SM | | |
| 35 | SPT | 11-26-42 (68) | | | - becomes moist |
| 40 | SPT | 23-50/6" | | | - becomes damp to moist, trace coarse grained sand |
| 41.0 | | | | | - Groundwater not encountered at time of drilling - Referenced elevations are approximate and based on Google Earth topography Bottom of borehole at 41.0 feet. |



PAGE 1 OF 1

PROJECT NAME Goose Prairie Photovoltaic (PV) Solar Array Project

PROJECT LOCATION Near Moxee, Yakima County Washington

COMPLETED 9/17/20

GROUND ELEVATION 1655 ft

HOLE SIZE 6 inches

DRILLING CONTRACTOR Western States Soil Conservation, Inc.

GROUND WATER LEVELS:

DRILLING METHOD CME 55 Track-Mounted Rig

AT TIME OF DRILLING ---

LOGGED BY KAH

CHECKED BY IM

AT END OF DRILLING ---

NOTES Approx. GPS Coords.: 46°32'23.50"N, 120°13'38.83"W

AFTER DRILLING ---

GENERAL BH / TP / WELL - GINT STD US LAB GDT - 10/12/20 10:41 - C:\USERS\YONG LEE\DROPBOX\5-ACTIVE PROJECTS\1220-1274 ONEENERGY GOOSE PRAIRIE SOLAR ARRAY NEAR MOXEE WA\220-1274 LOGS.GPJ

- Groundwater not encountered at time of drilling
- Referenced elevations are approximate and based on Google Earth topography

Bottom of borehole at 23.0 feet.



GN Northern, Inc.
722 N. 16th Avenue Suite 31
Yakima, Washington 98902
Telephone: (509) 248-9798
Fax: (509) 248-4220

BORING NUMBER B-5

PAGE 1 OF 1

CLIENT OER WA Solar 1, LLC
PROJECT NUMBER 220-1274
DATE STARTED 9/17/20 **COMPLETED** 9/17/20
DRILLING CONTRACTOR Western States Soil Conservation, Inc.
DRILLING METHOD CME 55 Track-Mounted Rig
LOGGED BY KAH **CHECKED BY** IM
NOTES Approx. GPS Coords.: 46°32'15.94"N, 120°13'39.72"W

PROJECT NAME Goose Prairie Photovoltaic (PV) Solar Array Project
PROJECT LOCATION Near Moxee, Yakima County Washington
GROUND ELEVATION 1616 ft **HOLE SIZE** 6 inches
GROUND WATER LEVELS:
AT TIME OF DRILLING ---
AT END OF DRILLING ---
AFTER DRILLING ---

GENERAL BH / TP / WELL - GINT STD US LAB.GDT - 10/12/20 10:41 - C:\USERS\YONG LEE\DROPBOX\ACTIVE PROJECTS\220-1274 ONEENERGY - GOOSE PRAIRIE SOLAR ARRAY - NEAR MOXEE WA\220-1274 LOGS.GPJ

| DEPTH (ft) | SAMPLE TYPE NUMBER | BLOW COUNTS (N VALUE) | U.S.C.S. | GRAPHIC LOG | MATERIAL DESCRIPTION |
|---------------|-----------------------|-----------------------------|----------|----------------|--|
| 0 | | | | | |
| 5 | SPT | 50 | | | SILTY GRAVEL WITH SAND, (GM) brown, dry, very dense |
| | SPT | 50/3" | GM | | |
| | SPT | 50/3" | | | |
| 10 | SPT | 50/4" | | | |
| | | | ML | | SILT WITH SAND (ML) / SANDY SILT, (ML) brown, fine grained, dry, very dense, (siltstone) [Ellensburg Formation] |
| 15 | SPT | 50/3" | GM | | SILTY GRAVEL WITH SAND, (GM) brown, dry, very dense |
| | | | | | |
| 20 | | | SM | | SILTY SAND, (SM) brown, dry, very dense, (sandstone) |
| | SPT | 50/1" | | | |

- Groundwater not encountered at time of drilling
- Referenced elevations are approximate and based on Google Earth topography
Bottom of borehole at 20.1 feet.



GN Northern, Inc.
722 N. 16th Avenue Suite 31
Yakima, Washington 98902
Telephone: (509) 248-9798
Fax: (509) 248-4220

BORING NUMBER B-6

PAGE 1 OF 1

CLIENT OER WA Solar 1, LLC

PROJECT NAME Goose Prairie Photovoltaic (PV) Solar Array Project

PROJECT NUMBER 220-1274

PROJECT LOCATION Near Moxee, Yakima County Washington

DATE STARTED 9/17/20

COMPLETED 9/17/20

GROUND ELEVATION 1501 ft

HOLE SIZE 6 inches

DRILLING CONTRACTOR Western States Soil Conservation, Inc.

GROUND WATER LEVELS:

DRILLING METHOD CME 55 Track-Mounted Rig

AT TIME OF DRILLING ---

LOGGED BY KAH

CHECKED BY IM

AT END OF DRILLING ---


NOTES Approx. GPS Coords.: 46°32'8.31"N, 120°14'18.63"W

AFTER DRILLING ---

GENERAL BH / TP / WELL - GINT STD US LAB.GDT - 10/12/20 10:41 - C:\USERS\YONG LEE\DROPBOX\ACTIVE PROJECTS\220-1274 ONEENERGY - GOOSE PRAIRIE SOLAR ARRAY - NEAR MOXEE WA\220-1274 LOGS.GPJ

| DEPTH (ft) | SAMPLE TYPE NUMBER | BLOW COUNTS (N VALUE) | U.S.C.S. | GRAPHIC LOG | MATERIAL DESCRIPTION |
|---------------|-----------------------|-----------------------------|----------|----------------|--|
| 0 | | | | | |
| | | | ML | | SILT, (ML) tan, dry, loose |
| | SPT | 4-18-11 (29) | | | 3.0 1498.0 |
| 5 | SPT | 50/6" | | | SILTY GRAVEL WITH SAND, (GM) brown, dry, medium dense |
| | | | | | - becomes very dense |
| | SPT | 50/5" | GM | | |
| 10 | SPT | 50/1" | | | |
| | | | | | 12.0 1489.0 |
| | | | | | SILTY SAND, (ML) light olive tan, damp, very dense, (sandstone) [Ellensburg Formation] |
| 15 | SPT | 12-23-44 (67) | | | |
| | | | ML | | |
| 20 | SPT | 12-20-25 (45) | | | - becomes Silt with Sand (ML) / Sandy Silt (ML), brown |
| 25 | SPT | 16-33-49 (82) | | | |
| | | | | | 26.5 1474.5 |

- Groundwater not encountered at time of drilling
- Referenced elevations are approximate and based on Google Earth topography
Bottom of borehole at 26.5 feet.



PAGE 1 OF 1

PROJECT NAME Goose Prairie Photovoltaic (PV) Solar Array Project

PROJECT LOCATION Near Moxee, Yakima County Washington

HOLE SIZE 6 inches

GROUND WATER LEVELS:

AT TIME OF DRILLING ---

AT END OF DRILLING ---

AFTER DRILLING ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | BLOW COUNTS (N VALUE) | TESTS | U.S.C.S. | GRAPHIC LOG | MATERIAL DESCRIPTION |
|---------------|-----------------------|-----------------------------|------------------------|----------|----------------|---|
| 0 | | | | | | |
| | | | | ML | | SILT, (ML) tan, dry, loose to medium dense |
| | | | | | 2.0 | 1578.0 |
| | SPT | 48-50 | | | | SILTY GRAVEL, (GM) brown, dry, very dense |
| 5 | | | | | | |
| | SPT | 50/3" | | | | |
| | | | | | | |
| | SPT | 50/3" | | | | |
| 10 | | | | GM | | |
| | SPT | 50/3" | | | | |
| | | | | | | |
| 15 | | | | | | |
| | SPT | 39-50/4" | MC = 3% Fines = 13% | | | - becomes Poorly Graded Gravel with Silt and Sand (GP-GM) |
| | | | | | | |
| | | | | | 19.0 | 1561.0 |
| 20 | | | | SM | | SILTY SAND, (SM) brown, fine grained, dry to damp, very dense, trace gravel (sandstone) [Ellensburg Formation] |
| | SPT | 50/3" | | | | |
| | | | | | | |
| | | | | | 22.0 | 1558.0 |
| | | | | GM | | SILTY GRAVEL WITH SAND, (GM) brown, dry to damp, very dense, with Silty Sand with Gravel (SM) |
| 25 | | | | | | |
| | SPT | 50/3" | | | 25.3 | 1554.8 |
| | | | | | | - Groundwater not encountered at time of drilling - Referenced elevations are approximate and based on Google Earth topography Bottom of borehole at 25.3 feet. |



GN Northern, Inc.
722 N. 16th Avenue Suite 31
Yakima, Washington 98902
Telephone: (509) 248-9798
Fax: (509) 248-4220

BORING NUMBER B-8

PAGE 1 OF 1

CLIENT OER WA Solar 1, LLC

PROJECT NAME Goose Prairie Photovoltaic (PV) Solar Array Project

PROJECT NUMBER 220-1274

PROJECT LOCATION Near Moxee, Yakima County Washington

DATE STARTED 9/18/20

COMPLETED 9/18/20

GROUND ELEVATION 1510 ft

HOLE SIZE 6 inches

DRILLING CONTRACTOR Western States Soil Conservation, Inc.

GROUND WATER LEVELS:

DRILLING METHOD CME 55 Track-Mounted Rig

AT TIME OF DRILLING ---

LOGGED BY KAH

CHECKED BY IM

AT END OF DRILLING ---

NOTES Approx. GPS Coords.: 46°31'56.31"N, 120°14'7.56"W

AFTER DRILLING ---

GENERAL BH / TP / WELL - GINT STD US LAB.GDT - 10/12/20 10:41 - C:\USERS\YONG LEE\DROPBOX\ACTIVE PROJECTS\220-1274 ONEENERGY - GOOSE PRAIRIE SOLAR ARRAY - NEAR MOXEE WA\220-1274 LOGS.GPJ

| DEPTH (ft) | SAMPLE TYPE NUMBER | BLOW COUNTS (N VALUE) | TESTS | U.S.C.S. | GRAPHIC LOG | MATERIAL DESCRIPTION |
|---------------|-----------------------|-----------------------------|------------------------|----------|----------------|--|
| 0 | | | | | | |
| | | | | ML | | SILT, (ML) tan, dry, loose |
| | | | | | 2.0 | 1508.0 |
| | SPT | 50/2" | | | | SILTY GRAVEL WITH SAND, (GM) light brown, dry, very dense |
| 5 | | | | GM | | |
| | SPT | 50/4" | | | | |
| | | | | | 8.5 | 1501.5 |
| 10 | | | | ML | | SILT WITH SAND, (ML) brown, moist, very dense, some Sandy Silt (ML) (siltstone) [Ellensburg Formation] |
| | SPT | 11-16-44 (60) | | | | |
| 15 | | | | | 14.5 | 1495.5 |
| | SPT | 17-23-26 (49) | | | | SILTY SAND, (SM) brown, fine grained, damp to moist, dense to very dense, (sandstone) |
| 20 | | | | SM | | |
| | SPT | 43-46-50 (96) | MC = 5% Fines = 15% | | | - becomes fine to medium grained, trace coarse grained sand |
| 25 | | | | | 26.5 | 1483.5 |
| | SPT | 12-17-22 (39) | | | | |

- Groundwater not encountered at time of drilling
- Referenced elevations are approximate and based on Google Earth topography

Bottom of borehole at 26.5 feet.



GN Northern, Inc.
722 N. 16th Avenue Suite 31
Yakima, Washington 98902
Telephone: (509) 248-9798
Fax: (509) 248-4220

BORING NUMBER B-9

PAGE 1 OF 1

CLIENT OER WA Solar 1, LLC

PROJECT NAME Goose Prairie Photovoltaic (PV) Solar Array Project

PROJECT NUMBER 220-1274

PROJECT LOCATION Near Moxee, Yakima County Washington

DATE STARTED 9/21/20

COMPLETED 9/21/20

GROUND ELEVATION 1502 ft

HOLE SIZE 6 inches

DRILLING CONTRACTOR Western States Soil Conservation, Inc.

GROUND WATER LEVELS:

DRILLING METHOD CME 55 Track-Mounted Rig

AT TIME OF DRILLING ---

LOGGED BY KAH

CHECKED BY IM

AT END OF DRILLING ---

NOTES Approx. GPS Coords.: 46°31'43.70"N, 120°13'57.42"W

AFTER DRILLING ---

GENERAL BH / TP / WELL - GINT STD US LAB.GDT - 10/12/20 10:41 - C:\USERS\YONG LEE\DROPBOX\ACTIVE PROJECTS\220-1274 ONEENERGY - GOOSE PRAIRIE SOLAR ARRAY - NEAR MOXEE WA\220-1274 LOGS.GPJ

| DEPTH (ft) | SAMPLE TYPE NUMBER | BLOW COUNTS (N VALUE) | U.S.C.S. | GRAPHIC LOG | MATERIAL DESCRIPTION |
|---------------|-----------------------|-----------------------------|----------|----------------|---|
| 0 | | | | | |
| | | | ML | | SILT, (ML) tan, dry, loose to medium dense |
| | | | | 2.0 | 1500.0 |
| | SPT | 50/6" | | | SILTY GRAVEL WITH SAND, (GM) tan, dry, very dense |
| 5 | | | | | - becomes dry to damp |
| | SPT | 50/5" | | | |
| | | | GM | | - becomes brown, damp |
| | SPT | 50/4" | | | |
| 10 | | | | | |
| | SPT | 50/3" | | | |
| | | | | 13.5 | 1488.5 |
| | | | | | SILTY SAND WITH GRAVEL, (SM) brown, damp, very dense, (sandstone) [Ellensburg Formation] |
| 15 | | | SM | | |
| | SPT | 50/5" | | | |
| | | | | 18.5 | 1483.5 |
| | | | | | SANDY SILT, (ML) brown, moist, medium dense, some Silty Sand (SM) and Silt with Sand (ML) (siltstone) |
| 20 | | | ML | | |
| | SPT | 7-8-8 (16) | | | |
| | | | | 26.2 | 1475.8 |
| | | | | | - becomes very dense |
| 25 | | | | | |
| | SPT | 27-35- 50/4" | | | |

- Groundwater not encountered at time of drilling
- Referenced elevations are approximate and based on Google Earth topography
Bottom of borehole at 26.2 feet.



GN Northern, Inc.
722 N. 16th Avenue Suite 31
Yakima, Washington 98902
Telephone: (509) 248-9798
Fax: (509) 248-4220

BORING NUMBER B-10

PAGE 1 OF 1

CLIENT OER WA Solar 1, LLC **PROJECT NAME** Goose Prairie Photovoltaic (PV) Solar Array Project
PROJECT NUMBER 220-1274 **PROJECT LOCATION** Near Moxee, Yakima County Washington
DATE STARTED 9/21/20 **COMPLETED** 9/21/20 **GROUND ELEVATION** 1461 ft **HOLE SIZE** 6 inches
DRILLING CONTRACTOR Western States Soil Conservation, Inc. **GROUND WATER LEVELS:**
DRILLING METHOD CME 55 Track-Mounted Rig **AT TIME OF DRILLING** ---
LOGGED BY KAH **CHECKED BY** IM **AT END OF DRILLING** ---
NOTES Approx. GPS Coords.: 46°31'44.71"N, 120°14'25.90"W **AFTER DRILLING** ---

GENERAL BH / TP / WELL - GINT STD US LAB.GDT - 10/12/20 10:41 - C:\USERS\YONG LEE\DROPBOX\5-ACTIVE PROJECTS\220-1274 ONEENERGY - GOOSE PRAIRIE SOLAR ARRAY - NEAR MOXEE WA\220-1274 LOGS.GPJ

| DEPTH (ft) | SAMPLE TYPE NUMBER | BLOW COUNTS (N VALUE) | U.S.C.S. | GRAPHIC LOG | MATERIAL DESCRIPTION |
|---------------|-----------------------|-----------------------------|----------|----------------|--|
| 0 | | | | | |
| | | | ML | | SILT, (ML) tan, dry, loose |
| | | | | 2.0 | 1459.0 |
| | ✕ SPT | 31-50/4" | | | SILTY GRAVEL WITH SAND, (GM) tan, dry, very dense |
| 5 | | | GM | | |
| | ✕ SPT | 50/4" | | | |
| | | | | 9.5 | 1451.5 |
| 10 | | | | | SILTY SAND, (SM) brown, fine grained, damp, very dense, (sandstone) [Ellensburg Formation] |
| | ✕ SPT | 50/5" | | | |
| 15 | | | SM | | - becomes moist, with Sandy Silt (ML) |
| | ✕ SPT | 20-45-50/5" | | | |
| 20 | | | | | - becomes damp to moist |
| | ✕ SPT | 35-50/3" | | | |
| 25 | | | | | - becomes moist |
| | ✕ SPT | 18-33-45 (78) | | 26.5 | 1434.5 |

- Groundwater not encountered at time of drilling
- Referenced elevations are approximate and based on Google Earth topography
Bottom of borehole at 26.5 feet.



GN Northern, Inc.
722 N. 16th Avenue Suite 31
Yakima, Washington 98902
Telephone: (509) 248-9798
Fax: (509) 248-4220

BORING NUMBER B-11

PAGE 1 OF 1

CLIENT OER WA Solar 1, LLC

PROJECT NAME Goose Prairie Photovoltaic (PV) Solar Array Project

PROJECT NUMBER 220-1274

PROJECT LOCATION Near Moxee, Yakima County Washington

DATE STARTED 9/21/20

COMPLETED 9/21/20

GROUND ELEVATION 1426 ft

HOLE SIZE 6 inches

DRILLING CONTRACTOR Western States Soil Conservation, Inc.

GROUND WATER LEVELS:

DRILLING METHOD CME 55 Track-Mounted Rig

AT TIME OF DRILLING ---

LOGGED BY KAH

CHECKED BY IM

AT END OF DRILLING ---

NOTES Approx. GPS Coords.: 46°31'51.57"N, 120°14'51.61"W

AFTER DRILLING ---

GENERAL BH / TP / WELL - GINT STD US LAB.GDT - 10/12/20 10:41 - C:\USERS\YONG LEE\DROPBOX\ACTIVE PROJECTS\220-1274 ONEENERGY - GOOSE PRAIRIE SOLAR ARRAY - NEAR MOXEE WA\220-1274 LOGS.GPJ

| DEPTH (ft) | SAMPLE TYPE NUMBER | BLOW COUNTS (N VALUE) | U.S.C.S. | GRAPHIC LOG | MATERIAL DESCRIPTION |
|---------------|-----------------------|-----------------------------|----------|----------------|---|
| 0 | | | | | |
| | | | ML | | SILT, (ML) tan, dry, loose |
| | SPT | 5-10-34 (44) | | | 3.5 1422.5 |
| 5 | | | GM | | SILTY GRAVEL WITH SAND, (GM) tan, dry, very dense |
| | SPT | 50/4" | | | |
| | | | | | 7.0 1419.0 |
| | SPT | 18-28-33 (61) | | | POORLY GRADED GRAVEL WITH SILT AND SAND, (GP-GM) brown, dry to damp, very dense |
| 10 | | | GP-GM | | |
| | SPT | 50/4" | | | |
| 15 | | | | | - becomes Silty Gravel (GM) |
| | SPT | 50/3" | | | |
| 20 | | | | | 20.0 1406.0 |
| | SPT | 16-15-16 (31) | | | SILT, (ML) olive tan, damp to moist, dense, (siltstone) [Ellensburg Formation] |
| | | | ML | | |
| 25 | | | | | - becomes moist |
| | SPT | 19-25-23 (48) | | | 26.5 1399.5 |

- Groundwater not encountered at time of drilling
- Referenced elevations are approximate and based on Google Earth topography
Bottom of borehole at 26.5 feet.



GN Northern, Inc.
722 N. 16th Avenue Suite 31
Yakima, Washington 98902
Telephone: (509) 248-9798
Fax: (509) 248-4220

BORING NUMBER B-12

PAGE 1 OF 1

CLIENT OER WA Solar 1, LLC

PROJECT NAME Goose Prairie Photovoltaic (PV) Solar Array Project

PROJECT NUMBER 220-1274

PROJECT LOCATION Near Moxee, Yakima County Washington

DATE STARTED 9/21/20 COMPLETED 9/21/20

GROUND ELEVATION 1418 ft HOLE SIZE 6 inches

DRILLING CONTRACTOR Western States Soil Conservation, Inc.

GROUND WATER LEVELS:

DRILLING METHOD CME 55 Track-Mounted Rig

AT TIME OF DRILLING ---

LOGGED BY KAH CHECKED BY IM

AT END OF DRILLING ---

NOTES Approx. GPS Coords.: 46°31'38.34"N, 120°14'52.47"W

AFTER DRILLING ---

GENERAL BH / TP / WELL - GINT STD US LAB.GDT - 10/12/20 10:41 - C:\USERS\YONG LEE\DROPBOX\ACTIVE PROJECTS\220-1274 ONEENERGY - GOOSE PRAIRIE SOLAR ARRAY - NEAR MOXEE WA\220-1274 LOGS.GPJ

| DEPTH (ft) | SAMPLE TYPE NUMBER | BLOW COUNTS (N VALUE) | U.S.C.S. | GRAPHIC LOG | MATERIAL DESCRIPTION |
|---------------|-----------------------|-----------------------------|----------|----------------|---|
| 0 | | | | | |
| | | | ML | | SILT, (ML) tan, dry, loose |
| | ▲ SPT | 25-50/3" | | | 2.8 |
| | | | | | SILTY GRAVEL WITH SAND, (GM) tan, dry, very dense |
| 5 | ▲ SPT | 50/4" | | | |
| | | | GM | | |
| | ▲ SPT | 50/6" | | | |
| 10 | ▲ SPT | 30-18-15 (33) | | | 11.0 |
| | | | | | SILT WITH CLAY, (ML) olive brown, moist, dense |
| 15 | ▲ SPT | 4-8-14 (22) | | | |
| | | | | | - becomes medium dense |
| 20 | ▲ SPT | 5-9-14 (23) | | | |
| | | | ML | | |
| 25 | ▲ SPT | 8-13-13 (26) | | | 26.5 |
| | | | | | 1391.5 |

- Groundwater not encountered at time of drilling
- Referenced elevations are approximate and based on Google Earth topography
Bottom of borehole at 26.5 feet.



GN Northern, Inc.
722 N. 16th Avenue Suite 31
Yakima, Washington 98902
Telephone: (509) 248-9798
Fax: (509) 248-4220

BORING NUMBER B-13

PAGE 1 OF 1

CLIENT OER WA Solar 1, LLC

PROJECT NAME Goose Prairie Photovoltaic (PV) Solar Array Project

PROJECT NUMBER 220-1274

PROJECT LOCATION Near Moxee, Yakima County Washington

DATE STARTED 9/21/20

COMPLETED 9/21/20

GROUND ELEVATION 1417 ft

HOLE SIZE 6 inches

DRILLING CONTRACTOR Western States Soil Conservation, Inc.

GROUND WATER LEVELS:

DRILLING METHOD CME 55 Track-Mounted Rig

AT TIME OF DRILLING ---

LOGGED BY KAH

CHECKED BY IM

AT END OF DRILLING ---


NOTES Approx. GPS Coords.: 46°31'25.60"N, 120°14'27.30"W

AFTER DRILLING ---

GENERAL BH / TP / WELL - GINT STD US LAB.GDT - 10/12/20 10:41 - C:\USERS\YONG LEE\DROPBOX\ACTIVE PROJECTS\220-1274 ONEENERGY - GOOSE PRAIRIE SOLAR ARRAY - NEAR MOXEE WA\220-1274 LOGS.GPJ

| DEPTH (ft) | SAMPLE TYPE NUMBER | BLOW COUNTS (N VALUE) | U.S.C.S. | GRAPHIC LOG | MATERIAL DESCRIPTION |
|---------------|-----------------------|-----------------------------|----------|----------------|---|
| 0 | | | | | |
| | | | ML | | SILT, (ML) tan, dry, loose |
| | | | | 2.0 | 1415.0 |
| | X SPT | 26-50/6" | GM | | SILTY GRAVEL WITH SAND, (GM) tan, dry, very dense |
| 5 | | | | | |
| | X SPT | 50/1" | | | |
| | | | GP-GM | | |
| | | | | 6.5 | 1410.5 |
| | X SPT | 50/5" | | | POORLY GRADED GRAVEL WITH SILT AND SAND, (GP-GM) brown, dry to damp, very dense |
| | | | | | |
| | | | | 9.0 | 1408.0 |
| 10 | | | GM | | SILTY GRAVEL WITH SAND, (GM) brown, damp to moist, very dense |
| | X SPT | 23-50/5" | | | - becomes dry to damp |
| | | | | | |
| | | | | 13.5 | 1403.5 |
| 15 | | | SM | | SILTY SAND, (SM) brown, damp to moist, very dense, (sandstone) [Ellensburg Formation] |
| | X SPT | 34-45-50 (95) | | | |
| | | | | | |
| | | | | 19.5 | 1397.5 |
| 20 | | | ML | | SANDY SILT, (ML) brown, moist, medium dense, some Silty Sand (SM) and Silt with Sand (ML) (siltstone) |
| | X SPT | 6-14-31 (45) | | | |
| | | | | | |
| 25 | | | | | |
| | X SPT | 17-38-50 (88) | | | |
| | | | | 26.5 | 1390.5 |

- Groundwater not encountered at time of drilling
- Referenced elevations are approximate and based on Google Earth topography
Bottom of borehole at 26.5 feet.



PAGE 1 OF 1

PROJECT NAME Goose Prairie Photovoltaic (PV) Solar Array Project

PROJECT LOCATION Near Moxee, Yakima County Washington

GROUND ELEVATION 1442 ft **HOLE SIZE** 6 inches

GROUND WATER LEVELS:

AT TIME OF DRILLING ---

AT END OF DRILLING ---

AFTER DRILLING ---

GENERAL BH / TP / WELL - GINT STD US LAB GDT - 10/12/20 10:41 - C:\USERS\YONG LEE\DROPBOX\5-ACTIVE PROJECTS\220-1274 ONEENERGY GOOSE PRAIRIE SOLAR ARRAY NEAR MOXEE WA\220-1274 LOGS.GPJ

- Groundwater not encountered at time of drilling
- Referenced elevations are approximate and based on Google Earth topography
Bottom of borehole at 26.5 feet.



GN Northern, Inc.
722 N. 16th Avenue Suite 31
Yakima, Washington 98902
Telephone: (509) 248-9798
Fax: (509) 248-4220

TEST PIT NUMBER TP-1

PAGE 1 OF 1

CLIENT OER WA Solar 1, LLC

PROJECT NAME Goose Prairie Photovoltaic (PV) Solar Array Project

PROJECT NUMBER 220-1274

PROJECT LOCATION Near Moxee, Yakima County Washington

DATE STARTED 8/26/20

COMPLETED 8/26/20

GROUND ELEVATION 1552 ft

TEST PIT SIZE 30 x 72 inches

EXCAVATION CONTRACTOR Valley Septic & Excavating

GROUND WATER LEVELS:

EXCAVATION METHOD Case 580 Super N Backhoe

AT TIME OF EXCAVATION ---

LOGGED BY MBB

CHECKED BY KAH

AT END OF EXCAVATION ---


NOTES Approx. GPS Coords.: 46°32'3.77"N, 120°13'49.52"W

AFTER EXCAVATION ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | U.S.C.S. | GRAPHIC LOG | MATERIAL DESCRIPTION |
|---------------|-----------------------|----------|----------------|---|
| 0.0 | | | | |
| 2.5 | | GM | | SILTY GRAVEL WITH SAND, (GM) brown, angular, dry, appears dense to very dense, with cobbles, trace boulders - becomes cemented, appears very dense - becomes reddish brown, moist |
| 5.0 | | | | |
| 6.0 | | | | 1546.0 |
| 7.5 | | SM | | SILTY SAND WITH GRAVEL, (SM) dark reddish brown, fine to medium grained, moist, appears very dense, (sandstone) [Ellensburg Formation] |
| 10.0 | | | | 1542.0 |

- Test pit terminated at ~10' BGS due to excavator refusal
- Groundwater not encountered at time of excavation
- Referenced elevations are approximate and based on Google Earth topography
Bottom of test pit at 10.0 feet.

GENERAL BH / TP / WELL - GINT STD US LAB.GDT - 10/12/20 10:41 - C:\USERS\YONG LEE\DROPBOX\5-ACTIVE PROJECTS\220-1274 ONEENERGY - GOOSE PRAIRIE SOLAR ARRAY - NEAR MOXEE WA\220-1274 LOGS.GPJ



PAGE 1 OF 1

PROJECT NAME Goose Prairie Photovoltaic (PV) Solar Array Project

PROJECT LOCATION Near Moxee, Yakima County Washington

GROUND ELEVATION 1639 ft **TEST PIT SIZE** 30 x 72 inches

GROUND WATER LEVELS:

AT TIME OF EXCAVATION ---

AT END OF EXCAVATION ---

AFTER EXCAVATION ---

MATERIAL DESCRIPTION

SILT WITH GRAVEL, (ML) brown, dry, appears loose

ML

2.5

SILTY SAND WITH GRAVEL, (SM) light pinkish tan, dry, appears very dense, (caliche)

1636.5

SM

4.0

SILTY GRAVEL WITH SAND, (GM) light pinkish tan, dry, appears very dense, highly cemented

1635.0

GM

8.0

- becomes moist

1631.0

- Test pit terminated at ~8' BGS due to excavator refusal
- Groundwater not encountered at time of excavation
- Referenced elevations are approximate and based on Google Earth topography
Bottom of test pit at 8.0 feet.

Bottom of test pit at 8.0 feet.

GENERAL BH / TP / WELL - GINT STD US LAB.GDT - 10/12/20 10:41 - C:\USERS\YONG LEE\DROPBOX\5-ACTIVE PROJECTS\220-1274 ONEENERGY GOOSE PRAIRIE SOLAR ARRAY. NEAR MOXEE WA\220-1274 LOGS.GPJ



GN Northern, Inc.
722 N. 16th Avenue Suite 31
Yakima, Washington 98902
Telephone: (509) 248-9798
Fax: (509) 248-4220

TEST PIT NUMBER TP-3

PAGE 1 OF 1

| | | | |
|-----------------------|--|---------------------------|---|
| CLIENT | OER WA Solar 1, LLC | PROJECT NAME | Goose Prairie Photovoltaic (PV) Solar Array Project |
| PROJECT NUMBER | 220-1274 | PROJECT LOCATION | Near Moxee, Yakima County Washington |
| DATE STARTED | 8/26/20 | COMPLETED | 8/26/20 |
| EXCAVATION CONTRACTOR | Valley Septic & Excavating | GROUND ELEVATION | 1589 ft |
| EXCAVATION METHOD | Case 580 Super N Backhoe | TEST PIT SIZE | 30 x 72 inches |
| LOGGED BY | MBB | CHECKED BY | KAH |
| NOTES | Approx. GPS Coords.: 46°32'15.77"N, 120°13'47.13"W | | |
| GROUND WATER LEVELS: | | AT TIME OF EXCAVATION --- | |
| | | AT END OF EXCAVATION --- | |
| | | AFTER EXCAVATION --- | |

| DEPTH (ft) | SAMPLE TYPE NUMBER | U.S.C.S. | GRAPHIC LOG | MATERIAL DESCRIPTION |
|---------------|-----------------------|----------|----------------|---|
| 0.0 | | | | |
| 2.5 | | | | |
| 5.0 | | ML | | SILT WITH SAND, (ML) brown, dry, appears medium dense |
| 7.5 | | | | |
| 10.0 | | | | - becomes cemented, trace cobbles |
| | | | | - becomes moderately cemented, with cobbles |
| 11.0 | | | | |

- Groundwater not encountered at time of excavation
- Referenced elevations are approximate and based on Google Earth topography
Bottom of test pit at 11.0 feet.

GENERAL BH / TP / WELL - GINT STD US LAB.GDT - 10/12/20 10:41 - C:\USERS\YONG LEE\DROPBOX\5-ACTIVE PROJECTS\220-1274 ONEENERGY - GOOSE PRAIRIE SOLAR ARRAY - NEAR MOXEE WA\220-1274 LOGS.GPJ

1578.0



GN Northern, Inc.
722 N. 16th Avenue Suite 31
Yakima, Washington 98902
Telephone: (509) 248-9798
Fax: (509) 248-4220

TEST PIT NUMBER TP-4

PAGE 1 OF 1

| | | | |
|-----------------------|---|---------------------------|---|
| CLIENT | OER WA Solar 1, LLC | PROJECT NAME | Goose Prairie Photovoltaic (PV) Solar Array Project |
| PROJECT NUMBER | 220-1274 | PROJECT LOCATION | Near Moxee, Yakima County Washington |
| DATE STARTED | 8/26/20 | COMPLETED | 8/26/20 |
| EXCAVATION CONTRACTOR | Valley Septic & Excavating | GROUND ELEVATION | 1559 ft |
| EXCAVATION METHOD | Case 580 Super N Backhoe | TEST PIT SIZE | 30 x 72 inches |
| LOGGED BY | MBB | CHECKED BY | KAH |
| NOTES | Approx. GPS Coords.: 46°32'14.29"N, 120°14'9.38"W | | |
| GROUND WATER LEVELS: | | AT TIME OF EXCAVATION --- | |
| | | AT END OF EXCAVATION --- | |
| | | AFTER EXCAVATION --- | |

| DEPTH (ft) | SAMPLE TYPE NUMBER | U.S.C.S. | GRAPHIC LOG | MATERIAL DESCRIPTION |
|---------------|-----------------------|----------|----------------|--|
| 0.0 | | | | |
| | | ML | | SILT WITH SAND, (ML) brown, dry, appears medium dense, trace gravel |
| 2.5 | | | | |
| | | GM | | SILTY GRAVEL WITH SAND, (GM) light brown, subangular, dry to damp, appears very dense, moderately to highly cemented |
| 5.0 | | | | |
| | | | | - becomes highly cemented |
| 6.0 | | | | |

- Test pit terminated at ~6' BGS due to excavator refusal
 - Groundwater not encountered at time of excavation
 - Referenced elevations are approximate and based on Google Earth topography
- Bottom of test pit at 6.0 feet.

GENERAL BH / TP / WELL - GINT STD US LAB.GDT - 10/12/20 10:41 - C:\USERS\YONG LEE\DROPBOX\5-ACTIVE PROJECTS\220-1274 ONEENERGY - GOOSE PRAIRIE SOLAR ARRAY - NEAR MOXEE WA\220-1274 LOGS.GPJ



GN Northern, Inc.
722 N. 16th Avenue Suite 31
Yakima, Washington 98902
Telephone: (509) 248-9798
Fax: (509) 248-4220

TEST PIT NUMBER TP-5

PAGE 1 OF 1

| | | | |
|-----------------------|--|---------------------------|---|
| CLIENT | OER WA Solar 1, LLC | PROJECT NAME | Goose Prairie Photovoltaic (PV) Solar Array Project |
| PROJECT NUMBER | 220-1274 | PROJECT LOCATION | Near Moxee, Yakima County Washington |
| DATE STARTED | 8/26/20 | COMPLETED | 8/26/20 |
| EXCAVATION CONTRACTOR | Valley Septic & Excavating | GROUND ELEVATION | 1531 ft |
| EXCAVATION METHOD | Case 580 Super N Backhoe | TEST PIT SIZE | 30 x 72 inches |
| LOGGED BY | MBB | CHECKED BY | KAH |
| NOTES | Approx. GPS Coords.: 46°31'59.45"N, 120°13'58.16"W | | |
| GROUND WATER LEVELS: | | AT TIME OF EXCAVATION --- | |
| | | AT END OF EXCAVATION --- | |
| | | AFTER EXCAVATION --- | |

| DEPTH (ft) | SAMPLE TYPE NUMBER | U.S.C.S. | GRAPHIC LOG | MATERIAL DESCRIPTION |
|---------------|-----------------------|----------|----------------|---|
| 0.0 | | | | |
| | | ML | | SILT WITH GRAVEL, (ML) brown, dry, appears medium dense |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| 1.5 | | | | 1529.5 |
| | | | | SILTY GRAVEL WITH SAND, (GM) light brown to white, subrounded to subangular, dry, appears very dense, with cobbles, highly cemented |
| 2.5 | | | | |
| | | GM | | - trace boulder |
| | | | | |
| | | | | |
| | | | | |
| 5.0 | | | | - becomes Poorly Graded Gravel with Silt and Sand (GP-GM) |
| | | | | |
| | | | | |
| | | | | |
| 6.0 | | | | 1525.0 |

- Test pit terminated at ~6' BGS due to excavator refusal
- Groundwater not encountered at time of excavation
- Referenced elevations are approximate and based on Google Earth topography
Bottom of test pit at 6.0 feet.



GN Northern, Inc.
722 N. 16th Avenue Suite 31
Yakima, Washington 98902
Telephone: (509) 248-9798
Fax: (509) 248-4220


TEST PIT NUMBER TP-6

PAGE 1 OF 1

| | | | |
|-----------------------|--|---------------------------|---|
| CLIENT | OER WA Solar 1, LLC | PROJECT NAME | Goose Prairie Photovoltaic (PV) Solar Array Project |
| PROJECT NUMBER | 220-1274 | PROJECT LOCATION | Near Moxee, Yakima County Washington |
| DATE STARTED | 8/26/20 | COMPLETED | 8/26/20 |
| EXCAVATION CONTRACTOR | Valley Septic & Excavating | GROUND ELEVATION | 1492 ft |
| EXCAVATION METHOD | Case 580 Super N Backhoe | TEST PIT SIZE | 30 x 72 inches |
| LOGGED BY | MBB | CHECKED BY | KAH |
| NOTES | Approx. GPS Coords.: 46°31'47.98"N, 120°14'10.63"W | | |
| GROUND WATER LEVELS: | | AT TIME OF EXCAVATION --- | |
| | | AT END OF EXCAVATION --- | |
| | | AFTER EXCAVATION --- | |

| DEPTH (ft) | SAMPLE TYPE NUMBER | U.S.C.S. | GRAPHIC LOG | MATERIAL DESCRIPTION |
|---------------|-----------------------|----------|----------------|---|
| 0.0 | | | | |
| 2.5 | | ML | | SILT WITH GRAVEL, (ML) brown, dry, appears medium dense |
| 3.5 | | | | |
| 5.0 | | GM | | SILTY GRAVEL WITH SAND, (GM) light brown to white, subrounded to subangular, dry, appears very dense, with cobbles, highly cemented, with caliche |
| 6.0 | | | | |
| | | | | 1488.5 |
| | | | | 1486.0 |

- Test pit terminated at ~6' BGS due to excavator refusal
- Groundwater not encountered at time of excavation
- Referenced elevations are approximate and based on Google Earth topography
Bottom of test pit at 6.0 feet.



PAGE 1 OF 1

PROJECT NAME Goose Prairie Photovoltaic (PV) Solar Array Project

PROJECT LOCATION Near Moxee, Yakima County Washington

GROUND ELEVATION 1475 ft **TEST PIT SIZE** 30 x 72 inches

GROUND WATER LEVELS:

AT TIME OF EXCAVATION ---

AT END OF EXCAVATION ---

AFTER EXCAVATION ---

[illegible]

- Test pit terminated at ~7' BGS due to excavator refusal
- Groundwater not encountered at time of excavation
- Referenced elevations are approximate and based on Google Earth topography
Bottom of test pit at 7.0 feet.

Bottom of test pit at 7.0 feet.

GENERAL BH / TP / WELL - GINT STD US LAB.GDT - 10/12/20 10:41 - C:\USERS\YONG LEE\DROPBOX\5-ACTIVE PROJECTS\220-1274 ONEENERGY GOOSE PRAIRIE SOLAR ARRAY, NEAR MOXEE WA\220-1274 LOGS.GPJ



GN Northern, Inc.
722 N. 16th Avenue Suite 31
Yakima, Washington 98902
Telephone: (509) 248-9798
Fax: (509) 248-4220

TEST PIT NUMBER TP-8

PAGE 1 OF 1

| | | | |
|-----------------------|--|---------------------------|---|
| CLIENT | OER WA Solar 1, LLC | PROJECT NAME | Goose Prairie Photovoltaic (PV) Solar Array Project |
| PROJECT NUMBER | 220-1274 | PROJECT LOCATION | Near Moxee, Yakima County Washington |
| DATE STARTED | 8/26/20 | COMPLETED | 8/26/20 |
| EXCAVATION CONTRACTOR | Valley Septic & Excavating | GROUND ELEVATION | 1443 ft |
| EXCAVATION METHOD | Case 580 Super N Backhoe | TEST PIT SIZE | 30 x 72 inches |
| LOGGED BY | MBB | CHECKED BY | KAH |
| NOTES | Approx. GPS Coords.: 46°31'34.25"N, 120°14'22.07"W | | |
| GROUND WATER LEVELS: | | AT TIME OF EXCAVATION --- | |
| | | AT END OF EXCAVATION --- | |
| | | AFTER EXCAVATION --- | |

| DEPTH (ft) | SAMPLE TYPE NUMBER | U.S.C.S. | GRAPHIC LOG | MATERIAL DESCRIPTION |
|---------------|-----------------------|----------|----------------|---|
| 0.0 | | | | |
| | | ML | | SILT WITH GRAVEL, (ML) brown, dry, appears medium dense |
| 2.5 | | | | |
| | | GM | | SILTY GRAVEL WITH SAND, (GM) light brown to white, subrounded to subangular, dry, appears very dense, with cobbles, highly cemented, with caliche |
| 5.0 | | | | |
| | | | | |
| 6.0 | | | | |
| | | | | |

- Test pit terminated at ~6' BGS due to excavator refusal
 - Groundwater not encountered at time of excavation
 - Referenced elevations are approximate and based on Google Earth topography
- Bottom of test pit at 6.0 feet.

GENERAL BH / TP / WELL - GINT STD US LAB.GDT - 10/12/20 10:41 - C:\USERS\YONG LEE\DROPBOX\ACTIVE PROJECTS\220-1274 ONEENERGY - GOOSE PRAIRIE SOLAR ARRAY - NEAR MOXEE WA\220-1274 LOGS.GPJ



GN Northern, Inc.
722 N. 16th Avenue Suite 31
Yakima, Washington 98902
Telephone: (509) 248-9798
Fax: (509) 248-4220

TEST PIT NUMBER TP-9

PAGE 1 OF 1

| | | | |
|-----------------------|--|---------------------------|---|
| CLIENT | OER WA Solar 1, LLC | PROJECT NAME | Goose Prairie Photovoltaic (PV) Solar Array Project |
| PROJECT NUMBER | 220-1274 | PROJECT LOCATION | Near Moxee, Yakima County Washington |
| DATE STARTED | 8/26/20 | COMPLETED | 8/26/20 |
| EXCAVATION CONTRACTOR | Valley Septic & Excavating | GROUND ELEVATION | 1429 ft |
| EXCAVATION METHOD | Case 580 Super N Backhoe | TEST PIT SIZE | 30 x 72 inches |
| LOGGED BY | MBB | CHECKED BY | KAH |
| NOTES | Approx. GPS Coords.: 46°31'44.39"N, 120°14'45.19"W | | |
| GROUND WATER LEVELS: | | AT TIME OF EXCAVATION --- | |
| | | AT END OF EXCAVATION --- | |
| | | AFTER EXCAVATION --- | |

| DEPTH (ft) | SAMPLE TYPE NUMBER | U.S.C.S. | GRAPHIC LOG | MATERIAL DESCRIPTION |
|---------------|-----------------------|----------|----------------|---|
| 0.0 | | | | |
| 2.5 | | ML | | SILT WITH GRAVEL, (ML) brown, dry, appears medium dense |
| 3.5 | | | | |
| 5.0 | | GM | | SILTY GRAVEL WITH SAND, (GM) light brown to white, subrounded to subangular, dry, appears very dense, with cobbles, highly cemented, with caliche |
| 6.0 | | | | |
| | | | | 1425.5 |
| | | | | 1423.0 |

- Test pit terminated at ~6' BGS due to excavator refusal
- Groundwater not encountered at time of excavation
- Referenced elevations are approximate and based on Google Earth topography
Bottom of test pit at 6.0 feet.



GN Northern, Inc.
722 N. 16th Avenue Suite 31
Yakima, Washington 98902
Telephone: (509) 248-9798
Fax: (509) 248-4220

TEST PIT NUMBER TP-10

PAGE 1 OF 1
















| | | | |
|-----------------------|--|---------------------------|---|
| CLIENT | OER WA Solar 1, LLC | PROJECT NAME | Goose Prairie Photovoltaic (PV) Solar Array Project |
| PROJECT NUMBER | 220-1274 | PROJECT LOCATION | Near Moxee, Yakima County Washington |
| DATE STARTED | 8/26/20 | COMPLETED | 8/26/20 |
| EXCAVATION CONTRACTOR | Valley Septic & Excavating | GROUND ELEVATION | 1471 ft |
| EXCAVATION METHOD | Case 580 Super N Backhoe | TEST PIT SIZE | 30 x 72 inches |
| LOGGED BY | MBB | CHECKED BY | KAH |
| NOTES | Approx. GPS Coords.: 46°31'56.46"N, 120°14'29.35"W | | |
| GROUND WATER LEVELS: | | AT TIME OF EXCAVATION --- | |
| | | AT END OF EXCAVATION --- | |
| | | AFTER EXCAVATION --- | |












| DEPTH (ft) | SAMPLE TYPE NUMBER | U.S.C.S. | GRAPHIC LOG | MATERIAL DESCRIPTION |
|---------------|-----------------------|----------|----------------|---|
| 0.0 | | | | |
| 2.5 | | ML | | SILT WITH GRAVEL, (ML) brown, dry, appears medium dense |
| 5.0 | | GM | | SILTY GRAVEL WITH SAND, (GM) light brown to white, subrounded to subangular, dry, appears very dense, with cobbles, highly cemented, with caliche |
| 6.5 | | | | |

- Test pit terminated at ~6.5' BGS due to excavator refusal
 - Groundwater not encountered at time of excavation
 - Referenced elevations are approximate and based on Google Earth topography
- Bottom of test pit at 6.5 feet.

KEY CHART

| RELATIVE DENSITY OR CONSISTENCY VERSUS SPT N-VALUE | | | | | |
|--|--------------|--|--------------------|--------------|---|
| COARSE-GRAINED SOILS | | | FINE-GRAINED SOILS | | |
| DENSITY | N (BLOWS/FT) | FIELD TEST | CONSISTENCY | N (BLOWS/FT) | FIELD TEST |
| Very Loose | 0 – 4 | Easily penetrated with ½-inch reinforcing rod pushed by hand | Very Soft | 0 – 2 | Easily penetrated several inches by thumb |
| Loose | 4 – 10 | Difficult to penetrate with ½-inch reinforcing rod pushed by hand | Soft | 2 – 4 | Easily penetrated one inch by thumb |
| Medium -Dense | 10 – 30 | Easily penetrated with ½-inch rod driven with a 5-lb hammer | Medium-Stiff | 4 – 8 | Penetrated over ½-inch by thumb with moderate effort |
| Dense | 30 – 50 | Difficult to penetrate with ½-inch rod driven with a 5-lb hammer | Stiff | 8 – 15 | Indented about ½-inch by thumb but penetrated with great effort |
| Very Dense | > 50 | penetrated only a few inches with ½-inch rod driven with a 5-lb hammer | Very Stiff | 15 – 30 | Readily indented by thumb |
| | | | Hard | > 30 | Indented with difficulty by thumbnail |

| USCS SOIL CLASSIFICATION | | | | | | |
|--------------------------|---|-------------------------------------|---|----|---|---|
| MAJOR DIVISIONS | | | GROUP DESCRIPTION | | | |
| Coarse-Grained Soils | Gravel and Gravelly Soils <50% coarse fraction passes #4 sieve | Gravel (with little or no fines) |  | GW | Well-graded Gravel | |
| | | |  | GP | Poorly Graded Gravel | |
| | | Gravel (with >12% fines) |  | GM | Silty Gravel | |
| | | |  | GC | Clayey Gravel | |
| | Sand and Sandy Soils >50% coarse fraction passes #4 sieve | Sand (with little or no fines) |  | SW | Well-graded Sand | |
| | | |  | SP | Poorly graded Sand | |
| | | Sand (with >12% fines) |  | SM | Silty Sand | |
| | | |  | SC | Clayey Sand | |
| Fine-Grained Soils | Silt and Clay Liquid Limit < 50 | |  | ML | Silt | |
| | | |  | CL | Lean Clay | |
| | | |  | OL | Organic Silt and Clay (low plasticity) | |
| | Silt and Clay Liquid Limit > 50 | |  | MH | Inorganic Silt | |
| | | |  | CH | Inorganic Clay | |
| | | |  | OH | Organic Clay and Silt (med. to high plasticity) | |
| Highly Organic Soils | | | | PT | Peat |  Top Soil |

| LOG SYMBOLS | | |
|---|----|--------------------------|
|  | 2S | 2" OD Split Spoon (SPT) |
|  | 3S | 3" OD Split Spoon |
|  | NS | Non-Standard Split Spoon |
|  | ST | Shelby Tube |
|  | CR | Core Run |
|  | BG | Bag Sample |
|  | TV | Torvane Reading |
|  | PP | Penetrometer Reading |
|  | NR | No Recovery |
|  | GW | Groundwater Table |
|  | | |

| MODIFIERS | |
|-------------|----------|
| DESCRIPTION | RANGE |
| Trace | <5% |
| Little | 5% – 12% |
| Some | >12% |

| MOISTURE CONTENT | |
|------------------|--|
| DESCRIPTION | FIELD OBSERVATION |
| Dry | Absence of moisture, dusty, dry to the touch |
| Moist | Damp but not visible water |
| Wet | Visible free water |

SOIL CLASSIFICATION INCLUDES

- Group Name
- Group Symbol
- Color
- Moisture content
- Density / consistency
- Cementation
- Particle size (if applicable)
- Odor (if present)
- Comments

| MAJOR DIVISIONS WITH GRAIN SIZE | | | | | | |
|---------------------------------|---------|--------|------|--------|--------|---------------|
| SIEVE SIZE | | | | | | |
| 12" | 3" | 3/4" | 4 | 10 | 40 | 200 |
| GRAIN SIZE (INCHES) | | | | | | |
| 12 | 3 | 0.75 | 0.19 | 0.079 | 0.0171 | 0.0029 |
| Boulders | Cobbles | Gravel | | Sand | | |
| | | Coarse | Fine | Coarse | Medium | Fine |
| | | | | | | Silt and Clay |

Conditions shown on boring and testpit logs represent our observations at the time and location of the fieldwork, modifications based on lab test, analysis, and geological and engineering judgment. These conditions may not exist at other times and locations, even in close proximity thereof. This information was gathered as part of our investigation, and we are not responsible for any use or interpretation of the information by others.

Appendix III
Laboratory Testing Results



GN Northern, Inc.
722 N. 16th Avenue Suite 31
Yakima, Washington 98902
Telephone: (509) 248-9798
Fax: (509) 248-4220


GRAIN SIZE DISTRIBUTION

CLIENT OER WA Solar 1, LLC

PROJECT NAME Goose Prairie Photovoltaic (PV) Solar Array Project

PROJECT NUMBER 220-1274

PROJECT LOCATION Near Moxee, Yakima County Washington



| COBBLES | GRAVEL | | SAND | | | SILT OR CLAY |
|---------|--------|------|--------|--------|------|--------------|
| | coarse | fine | coarse | medium | fine | |

| BOREHOLE | DEPTH | Classification | | | | | LL | PL | PI | Cc | Cu |
|----------|-------|---|-------|-------|-----|---------|-------|-------|----|-------|----|
| ● B-2 | 15.0 | SILT WITH SAND (ML) | | | | | | | | | |
| ☒ B-4 | 7.5 | SILT WITH SAND (ML) | | | | | | | | | |
| ▲ B-7 | 15.0 | POORLY GRADED GRAVEL WITH SILT AND SAND (GP-GM) | | | | | | | | | |
| ★ B-8 | 20.0 | SILTY SAND (SM) | | | | | | | | | |
| BOREHOLE | DEPTH | D100 | D60 | D30 | D10 | %Gravel | %Sand | %Silt | | %Clay | |
| ● B-2 | 15.0 | 4.75 | | | | 0.0 | 22.7 | 77.3 | | | |
| ☒ B-4 | 7.5 | 2 | | | | 0.0 | 16.7 | 83.3 | | | |
| ▲ B-7 | 15.0 | 37.5 | 8.564 | 1.197 | | 50.8 | 36.7 | 12.5 | | | |
| ★ B-8 | 20.0 | 9.5 | 0.718 | 0.247 | | 2.8 | 82.6 | 14.6 | | | |

GRAIN SIZE - TEMPLATE_JESSE.GDT - 10/12/20 10:33 - C:\USERS\YONG LEE\DROPBOX\5-ACTIVE PROJECTS\220-1274 ONEENERGY - GOOSE PRAIRIE SOLAR ARRAY, NEAR MOXEE WA\220-1274 LOGS.GPJ

Appendix IV
Soil Corrosivity Testing Results

Am Test Inc.
13600 NE 126TH PL
Suite C
Kirkland, WA 98034
(425) 885-1664
www.amtestlab.com



**Professional
Analytical
Services**

ANALYSIS REPORT

GN NORTHERN, INC.
11115 E MONTGOMERY AVE
SPOKANE VALLEY, WA 99206
Attention: KARL HARMON
Project Name: GOOSE PRAIRIE SOLAR ARRAY
Project #: 220-1274
PO Number: 220-1274
All results reported on an as received basis.

Date Received: 09/03/20
Date Reported: 9/23/20

AMTEST Identification Number 20-A013972
Client Identification TP1 @ 4'
Sampling Date 08/26/20

Conventionals

| PARAMETER | RESULT | UNITS | Q | D.L. | METHOD | ANALYST | DATE |
|-----------------|--------|---------|---|------|---------------|---------|----------|
| pH | 8.16 | Unit | | | ASTM G51 | KF | 09/08/20 |
| Resistivity | 3300 | ohms cm | | 100 | ASTM G-187 | KF | 09/08/20 |
| Redox Potential | 359. | unit | | 200 | ASTM D1498-76 | KF | 09/08/20 |

Minerals

| PARAMETER | RESULT | UNITS | Q | D.L. | METHOD | ANALYST | DATE |
|-----------|--------|-------|---|------|------------|---------|----------|
| Chloride | 30. | ug/g | | 10 | ASTM D4327 | AY | 09/16/20 |
| Sulfate | < 10 | ug/g | | 10 | ASTM D4327 | AY | 09/16/20 |

Miscellaneous

| PARAMETER | RESULT | UNITS | Q | D.L. | METHOD | ANLST | DATE |
|-----------|----------|-------|---|------|----------------------|-------|----------|
| Sulfide | NEGATIVE | | | | Acetate Paper Acetat | KF | 09/08/20 |

GN NORTHERN, INC.
Project Name: GOOSE PRAIRIE SOLAR ARRAY
AmTest ID: 20-A013973

AMTEST Identification Number **20-A013973**
Client Identification **TP3 @ 4'**
Sampling Date **08/26/20**

Conventionals

| PARAMETER | RESULT | UNITS | Q | D.L. | METHOD | ANALYST | DATE |
|-----------------|--------|---------|---|------|---------------|---------|----------|
| pH | 8.35 | Unit | | | ASTM G51 | KF | 09/08/20 |
| Resistivity | 2400 | ohms cm | | 100 | ASTM G-187 | KF | 09/08/20 |
| Redox Potential | 379. | unit | | 200 | ASTM D1498-76 | KF | 09/08/20 |

Minerals

| PARAMETER | RESULT | UNITS | Q | D.L. | METHOD | ANALYST | DATE |
|-----------|--------|-------|---|------|------------|---------|----------|
| Chloride | 64. | ug/g | | 10 | ASTM D4327 | AY | 09/16/20 |
| Sulfate | < 10 | ug/g | | 10 | ASTM D4327 | AY | 09/16/20 |

Miscellaneous

| PARAMETER | RESULT | UNITS | Q | D.L. | METHOD | ANLST | DATE |
|-----------|----------|-------|---|------|----------------------|-------|----------|
| Sulfide | NEGATIVE | | | | Acetate Paper Acetat | KF | 09/08/20 |

GN NORTHERN, INC.
Project Name: GOOSE PRAIRIE SOLAR ARRAY
AmTest ID: 20-A013974

AMTEST Identification Number **20-A013974**
Client Identification **TP8 @ 1.5'**
Sampling Date **08/26/20**

Conventionals


| PARAMETER | RESULT | UNITS | Q | D.L. | METHOD | ANALYST | DATE |
|-----------------|--------|---------|---|------|---------------|---------|----------|
| pH | 7.33 | Unit | | | ASTM G51 | KF | 09/08/20 |
| Resistivity | 8200 | ohms cm | | 100 | ASTM G-187 | KF | 09/08/20 |
| Redox Potential | 414. | unit | | 200 | ASTM D1498-76 | KF | 09/08/20 |

Minerals


| PARAMETER | RESULT | UNITS | Q | D.L. | METHOD | ANALYST | DATE |
|-----------|--------|-------|---|------|------------|---------|----------|
| Chloride | < 10 | ug/g | | 10 | ASTM D4327 | AY | 09/16/20 |
| Sulfate | 17. | ug/g | | 10 | ASTM D4327 | AY | 09/16/20 |

Miscellaneous

| PARAMETER | RESULT | UNITS | Q | D.L. | METHOD | ANLST | DATE |
|-----------|----------|-------|---|------|----------------------|-------|----------|
| Sulfide | NAGATIVE | | | | Acetate Paper Acetat | KF | 09/08/20 |


Kathy Fugiel
President

Appendix V
Results of Electrical Resistivity Testing



Global Geophysics

P.O. Box 2229
Redmond, WA 98073-2229
Tel: 425-890-4321
Fax: 206-582-0838

September 8, 2020

Our ref: 110-0901.000

GN Northern Inc.
722 North 16th Avenue, Suite 31
Yakima, WA 98902

Attention: Mr. Imran Magsi

RE: REPORT FOR ELECTRICAL RESISTIVITY SURVEY IN MOXEE, WA

This letter report presents the results of the geophysical surveys performed by Global Geophysics. The survey was carried out on September 2, 2020 in Moxee, WA. The objective of the survey was to measure the soil resistivity for grounding design.

GEOPHYSICAL METHODS AND FIELD PROCEDURES

Electrical Resistivity

The electrical resistivity sounding technique measures the differences in the electrical properties of geologic materials. These differences can result from variations in lithology, water content, and pore-water chemistry. The method involves transmitting an electric current into the ground between two electrodes and measuring the voltage between two other electrodes. The direct measurement is the apparent resistivity of the area beneath the electrodes. The measurements include deeper layers as the electrode spacing is increased.

The data were acquired with an AGI SuperSting resistivity meter, along E-W and N-S directions.

RESULTS

The line layout is shown below



Location: Moxee WA

Supplier: Conducted by Global Geophysics, P.O. Box 2229, Redmond, WA, 98073. Tel. 425-890-4321; email: Jliu@GlobalGeophysics.com;

Date of Test: September 2, 2020

Test Type: In situ

Manufacturer and model: AGI SuperSting

Date of last meter calibration: April, 2020

Ambient temperature: 85-95 F

Weather condition: Sunny

Recent precipitation: None

Soil composition: Sand

Difficulty of inserting the electrodes: Easy

Terrain condition: Flat open area with minimal vegetation

Lead cable size: 16 gauge copper wires

Electrode: 3/4 inch in diameter, 30 inch long stainless steel

Sounding Name: Moxee 1- EW

| Electrode Spacing "a" (ft) | Source Voltage (V) | I Injected (mA) | Apparent Resistance (ohm) | Apparent Resistivity (ohm-m) |
|-------------------------------|-----------------------|-----------------|------------------------------|---------------------------------|
| 1 | 400 | 8.00 | 34.900 | 66.85 |
| 2 | 400 | 13.00 | 9.1000 | 34.86 |
| 3 | 400 | 8.00 | 7.5000 | 43.10 |
| 5 | 400 | 14.00 | 5.2000 | 49.80 |
| 7 | 400 | 14.00 | 4.3000 | 57.66 |
| 10 | 400 | 17.00 | 2.9000 | 55.55 |
| 30 | 400 | 18.00 | 0.7000 | 40.23 |
| 50 | 400 | 24.00 | 0.3500 | 33.52 |

Test Type: In situ

Supplier: Conducted by Global Geophysics, P.O. Box 2229, Redmond, WA, 98073. Tel. 425-890-4321; email: Jliu@GlobalGeophysics.com;

Manufacturer and model: AGI SuperSting

Date of last meter calibration: April, 2020

Ambient temperature: 85-95 F

Weather condition: Sunny

Recent precipitation: None

Soil composition: Sand

Difficulty of inserting the electrodes: Easy

Terrain condition: Flat open area with minimal vegetation

Lead cable size: 16 gauge copper wires

Electrode: 3/4 inch in diameter, 30 inch long stainless steel

Sounding Name: Moxee 1 -NS

| Electrode Spacing "a" (ft) | Source Voltage (V) | I Injected (mA) | Apparent Resistance (ohm) | Apparent Resistivity (ohm-m) |
|-------------------------------|-----------------------|-----------------|------------------------------|---------------------------------|
| 1 | 400 | 8.00 | 34.865 | 66.79 |
| 2 | 400 | 13.00 | 8.9993 | 34.48 |
| 3 | 400 | 8.00 | 7.0532 | 40.53 |
| 5 | 400 | 14.00 | 5.0870 | 48.72 |
| 7 | 400 | 14.00 | 4.2257 | 56.66 |
| 10 | 400 | 17.00 | 2.9217 | 55.97 |
| 30 | 400 | 18.00 | 0.6761 | 38.85 |
| 50 | 400 | 24.00 | 0.3192 | 30.57 |

Location: Moxee WA

Supplier: Conducted by Global Geophysics, P.O. Box 2229, Redmond, WA, 98073. Tel. 425-890-4321; email: Jliu@GlobalGeophysics.com;

Date of Test: September 2, 2020

Test Type: In situ

Manufacturer and model: AGI SuperSting

Date of last meter calibration: April, 2020

Ambient temperature: 85-95 F

Weather condition: Sunny

Recent precipitation: None

Soil composition: Sand

Difficulty of inserting the electrodes: Easy

Terrain condition: Flat open area with minimal vegetation

Lead cable size: 16 gauge copper wires

Electrode: 3/4 inch in diameter, 30 inch long stainless steel

Sounding Name: Moxee 2- EW

| Electrode Spacing "a" (ft) | Source Voltage (V) | I Injected (mA) | Apparent Resistance (ohm) | Apparent Resistivity (ohm-m) |
|-------------------------------|-----------------------|-----------------|------------------------------|---------------------------------|
| 1 | 400 | 7.00 | 17.4300 | 33.39 |
| 2 | 400 | 12.00 | 9.6800 | 37.09 |
| 3 | 400 | 11.00 | 7.0810 | 40.69 |
| 5 | 400 | 11.00 | 5.1580 | 49.40 |
| 7 | 400 | 10.00 | 4.4420 | 59.56 |
| 10 | 400 | 21.00 | 2.7530 | 52.74 |
| 30 | 400 | 96.00 | 0.5246 | 30.15 |
| 50 | 400 | 35.00 | 0.1645 | 15.76 |

Test Type: In situ

Supplier: Conducted by Global Geophysics, P.O. Box 2229, Redmond, WA, 98073. Tel. 425-890-4321; email: Jliu@GlobalGeophysics.com;

Manufacturer and model: AGI SuperSting

Date of last meter calibration: April, 2020

Ambient temperature: 85-95 F

Weather condition: Sunny

Recent precipitation: None

Soil composition: Sand

Difficulty of inserting the electrodes: Easy

Terrain condition: Flat open area with minimal vegetation

Lead cable size: 16 gauge copper wires

Electrode: 3/4 inch in diameter, 30 inch long stainless steel

Sounding Name: Moxee 2 -NS

| Electrode Spacing "a" (ft) | Source Voltage (V) | I Injected (mA) | Apparent Resistance (ohm) | Apparent Resistivity (ohm-m) |
|-------------------------------|-----------------------|-----------------|------------------------------|---------------------------------|
| 1 | 400 | 7.00 | 17.5600 | 33.64 |
| 2 | 400 | 12.00 | 9.7000 | 37.16 |
| 3 | 400 | 11.00 | 7.1000 | 40.80 |
| 5 | 400 | 11.00 | 5.2000 | 49.80 |
| 7 | 400 | 10.00 | 4.4000 | 59.00 |
| 10 | 400 | 21.00 | 2.8000 | 53.64 |
| 30 | 400 | 96.00 | 0.5300 | 30.46 |
| 50 | 400 | 35.00 | 0.1800 | 17.24 |

CLOSURE

Global Geophysics services will be conducted in a manner consistent with the level of care and skill ordinarily exercised by other members of the geophysical community currently practicing under similar conditions subject to the time limits and financial and physical constraints applicable to the services.

We appreciate the opportunity to work with you on this project, and we hope that you find the results of the geophysical survey useful to your investigation. If you have any questions regarding this report, please call the undersigned at 425-890-4321. We look forward to providing you with additional geophysical services in the future.

Sincerely,

Global Geophysics.

A handwritten signature in black ink, appearing to read 'John', with a stylized flourish extending from the end.

John Liu, Ph.D., R.G.
Principal Geophysicist

Appendix VI
Results of Thermal Resistivity Testing

TRT Sampling Map





21239 FM529 Rd., Bldg F
Cypress, Texas 77433
Tel: 281-985-9344
Fax: 832-427-1752
www.geothermusa.com
info@geothermusa.com

September 25, 2020

GN Northern

722 No. 16th Ave, Ste. 31
Yakima, WA 98902
Attn: Max Barnett, GIT

**Re: Thermal Analysis of Native Samples
Goose Prairie Solar Array - Moxee, WA (PO No. 220-1274)**

The following is the report of thermal dryout characterization tests conducted on three (3) soil samples sent to our laboratory.

Thermal Dryout Tests: The samples were tested at the optimum moisture content and 90% of the maximum dry density provided by **GN Northern**. The tests were conducted in accordance with the IEEE standard 442-2017. The results are tabulated below, and the thermal dryout curves are presented in **Figures 1 to 3**.

Sample ID, Description, Thermal Resistivity, Moisture Content and Density

| Sample ID | Description (GN Northern) | Thermal Resistivity (°C-cm/W) | | Moistur e Content (%) | Dry Density (lb/ft ³) |
|---------------|------------------------------|-------------------------------------|-----|--------------------------------|---|
| | | Wet | Dry | | |
| TRT #1 @ 3-ft | Silty gravel with sand | 91 | 276 | 9 | 110 |
| TRT #2 @ 3-ft | Silty gravel with sand | 98 | 290 | 9 | 106 |
| TRT #3 @ 3-ft | Silty gravel with sand | 110 | 309 | 11 | 98 |

Comments: The thermal characteristic depicted in the dryout curves apply for the soils at their respective test dry density.


Please contact us if you have any questions or if we can be of further assistance.

Geotherm USA

Nimesh Patel

COOL SOLUTIONS FOR UNDERGROUND POWER CABLES
THERMAL SURVEYS, CORRECTIVE BACKFILLS & INSTRUMENTATION


Serving the electric power industry since 1978



GN Northern (PO No. 220-1274)
Thermal Analysis of Native Soil
Goose Prairie Solar Array, Moxee, WA

September 2020


Figure 1



GN Northern (PO No. 220-1274)
 Thermal Analysis of Native Soil
 Goose Prairie Solar Array, Moxee, WA

September 2020

Figure 2



GN Northern (PO No. 220-1274)
 Thermal Analysis of Native Soil
 Goose Prairie Solar Array, Moxee, WA

September 2020

Figure 3

Appendix VII
Site & Exploration Photographs



View of site conditions looking south from near Den Beste Rd



View of site conditions looking NE from near test pit TP-1



Exposed subsurface soil profile within test pit TP-1



Exposed subsurface soil profile within test pit TP-2




Exposed subsurface soil profile within test pit TP-3



Exposed subsurface soil profile within test pit TP-4



Exposed subsurface soil profile within test pit TP-5



Exposed subsurface soil profile within test pit TP-6



Excavation and spoils at test pit TP-7



Exposed subsurface soil profile within test pit TP-7



Exposed subsurface soil profile within test pit TP-8



Exposed subsurface soil profile within test pit TP-9




Exposed subsurface soil profile within test pit TP-10



Infiltration test setup at P-1



Infiltration test setup at P-3



Drilling at boring B-1, looking northeast



Split-spoon sample obtained from boring B-1 at 15' BGS



Drilling at boring B-4, looking south



View of conditions in northeastern portion of site, looking east



View of conditions in northeastern portion of site, looking northeast



View of conditions in northeastern portion of site, looking northeast



View of conditions in northeastern portion of site, looking south



View of conditions in northeastern portion of site



View of conditions in northeastern portion of site, looking south



View of conditions in northeastern portion of site, looking east



View of conditions in northeastern portion of site, looking northeast



View of conditions in northeastern portion of site, looking northeast



View of conditions in northeastern portion of site



View of conditions in northeastern portion of site, looking southeast



View of conditions in northeastern portion of site, looking south

Appendix VIII
NRCS Soil Survey



United States
Department of
Agriculture

NRCS

Natural
Resources
Conservation
Service

A product of the National
Cooperative Soil Survey,
a joint effort of the United
States Department of
Agriculture and other
Federal agencies, State
agencies including the
Agricultural Experiment
Stations, and local
participants


Custom Soil Resource Report for **Yakima County Area, Washington**

**Goose Prairie Solar Array, near
Moxee, WA**




October 8, 2020

Custom Soil Resource Report Soil Map



Map Scale: 1:16,800 if printed on A portrait (8.5" x 11") sheet.



Map projection: Web Mercator Corner coordinates: WGS84 Edge ticks: UTM Zone 10N WGS84

Yakima County Area, Washington

36—Finley cobbly fine sandy loam, 0 to 5 percent slopes

Map Unit Setting

National map unit symbol: 29sx

Elevation: 300 to 1,500 feet

Mean annual precipitation: 6 to 9 inches

Mean annual air temperature: 48 to 50 degrees F

Frost-free period: 135 to 180 days

Farmland classification: Not prime farmland

Map Unit Composition

Finley, cobbly, and similar soils: 100 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Finley, Cobbly

Setting

Landform: Terraces, alluvial fans

Parent material: Alluvium

Typical profile

H1 - 0 to 4 inches: cobbly fine sandy loam

H2 - 4 to 14 inches: fine sandy loam

H3 - 14 to 30 inches: very gravelly loam

H4 - 30 to 60 inches: extremely gravelly loamy sand

Properties and qualities

Slope: 0 to 5 percent

Depth to restrictive feature: 20 to 40 inches to strongly contrasting textural stratification

Drainage class: Well drained

Capacity of the most limiting layer to transmit water (Ksat): High (1.98 to 5.95 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None

Frequency of ponding: None

Calcium carbonate, maximum content: 20 percent

Maximum salinity: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Available water capacity: Low (about 3.2 inches)

Interpretive groups

Land capability classification (irrigated): 4s

Land capability classification (nonirrigated): 6s

Hydrologic Soil Group: A

Ecological site: R007XY501WA - SANDY 6-10 PZ

Hydric soil rating: No

65—Kiona stony silt loam, 15 to 45 percent slopes

Map Unit Setting

National map unit symbol: 29ty

Elevation: 400 to 2,500 feet

Mean annual precipitation: 6 to 9 inches

Mean annual air temperature: 48 to 54 degrees F

Frost-free period: 140 to 210 days

Farmland classification: Not prime farmland

Map Unit Composition

Kiona and similar soils: 100 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Kioma

Setting

Landform: Hillslopes

Parent material: Loess and colluvium derived from basalt

Typical profile

H1 - 0 to 5 inches: stony silt loam

H2 - 5 to 14 inches: very cobbly loam

H3 - 14 to 60 inches: very cobbly silt loam

Properties and qualities

Slope: 15 to 45 percent

Depth to restrictive feature: More than 80 inches

Drainage class: Well drained

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high
(0.57 to 1.98 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None

Frequency of ponding: None

Calcium carbonate, maximum content: 35 percent

Maximum salinity: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Available water capacity: Low (about 4.9 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 6e

Hydrologic Soil Group: B

Ecological site: R007XY102WA - LOAMY 6-10 PZ

Hydric soil rating: No

68—Lickskillet very stony silt loam, 5 to 45 percent slopes

Map Unit Setting

National map unit symbol: 29v1

Elevation: 200 to 3,600 feet

Mean annual precipitation: 10 to 16 inches

Mean annual air temperature: 45 to 52 degrees F

Frost-free period: 100 to 180 days

Farmland classification: Not prime farmland

Map Unit Composition

Lickskillet and similar soils: 100 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Lickskillet

Setting

Landform: Hillslopes, ridges

Parent material: Residuum and colluvium weathered from basalt, and loess

Typical profile

H1 - 0 to 3 inches: silt loam

H2 - 3 to 20 inches: very gravelly loam, very cobbly loam

H2 - 3 to 20 inches: unweathered bedrock

H3 - 20 to 24 inches:

Properties and qualities

Slope: 5 to 45 percent

Depth to restrictive feature: 12 to 20 inches to lithic bedrock

Drainage class: Well drained

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high
(0.57 to 1.98 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None

Frequency of ponding: None

Calcium carbonate, maximum content: 5 percent

Maximum salinity: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Available water capacity: Low (about 3.8 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 7s

Hydrologic Soil Group: C

Ecological site: R008XY201WA - DRY STONY 10-16 PZ

Hydric soil rating: No

83—Moxee silt loam, 2 to 15 percent slopes

Map Unit Setting

National map unit symbol: 29vl
Elevation: 900 to 2,000 feet
Mean annual precipitation: 8 to 12 inches
Mean annual air temperature: 48 to 50 degrees F
Frost-free period: 125 to 160 days
Farmland classification: Not prime farmland

Map Unit Composition

Moxee and similar soils: 95 percent
Minor components: 5 percent
Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Moxee

Setting

Parent material: Loess

Typical profile

H1 - 0 to 7 inches: silt loam
H2 - 7 to 11 inches: silt loam
H3 - 11 to 18 inches: gravelly silt loam
H4 - 18 to 22 inches: cemented material

Properties and qualities

Slope: 2 to 15 percent
Depth to restrictive feature: 10 to 20 inches to duripan
Drainage class: Well drained
Capacity of the most limiting layer to transmit water (Ksat): Very low to moderately low (0.00 to 0.06 in/hr)
Depth to water table: More than 80 inches
Frequency of flooding: None
Frequency of ponding: None
Calcium carbonate, maximum content: 15 percent
Maximum salinity: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)
Available water capacity: Low (about 3.4 inches)

Interpretive groups

Land capability classification (irrigated): 6s
Land capability classification (nonirrigated): 6s
Hydrologic Soil Group: D
Ecological site: R008XY201WA - DRY STONY 10-16 PZ
Hydric soil rating: No

Minor Components

Riverwash

Percent of map unit: 5 percent
Landform: Alluvial cones
Hydric soil rating: Yes

93—Pits

Map Unit Composition

Pits: 100 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Pits

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 8

Hydric soil rating: No

101—Ritzville silt loam, 8 to 15 percent slopes

Map Unit Setting

National map unit symbol: 29p1

Elevation: 800 to 3,000 feet

Mean annual precipitation: 9 to 12 inches

Mean annual air temperature: 48 to 52 degrees F

Frost-free period: 100 to 180 days

Farmland classification: Farmland of unique importance

Map Unit Composition

Ritzville and similar soils: 100 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Ritzville

Setting

Landform: Hillslopes

Parent material: Loess

Typical profile

H1 - 0 to 7 inches: silt loam

H2 - 7 to 37 inches: silt loam

H3 - 37 to 60 inches: silt loam

Properties and qualities

Slope: 8 to 15 percent

Depth to restrictive feature: More than 80 inches

Drainage class: Well drained

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high
(0.57 to 1.98 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None

Frequency of ponding: None

Custom Soil Resource Report

Calcium carbonate, maximum content: 15 percent

Maximum salinity: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Available water capacity: High (about 12.0 inches)

Interpretive groups

Land capability classification (irrigated): 4e

Land capability classification (nonirrigated): 3e

Hydrologic Soil Group: B

Ecological site: R008XY102WA

Hydric soil rating: No

187—Willis silt loam, 2 to 5 percent slopes

Map Unit Setting

National map unit symbol: 29s2

Elevation: 1,000 to 3,000 feet

Mean annual precipitation: 9 to 12 inches

Mean annual air temperature: 48 to 50 degrees F

Frost-free period: 125 to 180 days

Farmland classification: Farmland of statewide importance

Map Unit Composition

Willis and similar soils: 100 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Willis

Setting

Parent material: Loess

Typical profile

H1 - 0 to 6 inches: silt loam

H2 - 6 to 22 inches: silt loam

H3 - 22 to 34 inches: silt loam

H4 - 34 to 38 inches: cemented material

Properties and qualities

Slope: 2 to 5 percent

Depth to restrictive feature: 20 to 40 inches to duripan

Drainage class: Well drained

Capacity of the most limiting layer to transmit water (Ksat): Very low to moderately low (0.00 to 0.06 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None

Frequency of ponding: None

Calcium carbonate, maximum content: 10 percent

Maximum salinity: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Available water capacity: Moderate (about 6.7 inches)

Interpretive groups

Land capability classification (irrigated): 3e

Land capability classification (nonirrigated): 3e

Hydrologic Soil Group: C

Custom Soil Resource Report

Ecological site: R008XY102WA

Hydric soil rating: No

188—Willis silt loam, 5 to 8 percent slopes

Map Unit Setting

National map unit symbol: 29s3

Elevation: 1,000 to 3,000 feet

Mean annual precipitation: 9 to 12 inches

Mean annual air temperature: 48 to 50 degrees F

Frost-free period: 125 to 180 days

Farmland classification: Farmland of statewide importance

Map Unit Composition

Willis and similar soils: 100 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Willis

Setting

Parent material: Loess

Typical profile

H1 - 0 to 6 inches: silt loam

H2 - 6 to 22 inches: silt loam

H3 - 22 to 34 inches: silt loam

H4 - 34 to 38 inches: cemented material

Properties and qualities

Slope: 5 to 8 percent

Depth to restrictive feature: 20 to 40 inches to duripan

Drainage class: Well drained

Capacity of the most limiting layer to transmit water (Ksat): Very low to moderately low (0.00 to 0.06 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None

Frequency of ponding: None

Calcium carbonate, maximum content: 10 percent

Maximum salinity: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Available water capacity: Moderate (about 6.7 inches)

Interpretive groups

Land capability classification (irrigated): 3e

Land capability classification (nonirrigated): 3e

Hydrologic Soil Group: C

Ecological site: R008XY102WA

Hydric soil rating: No

189—Willis silt loam, 8 to 15 percent slopes

Map Unit Setting

National map unit symbol: 29s4
Elevation: 1,000 to 3,000 feet
Mean annual precipitation: 9 to 12 inches
Mean annual air temperature: 48 to 50 degrees F
Frost-free period: 125 to 180 days
Farmland classification: Farmland of unique importance

Map Unit Composition

Willis and similar soils: 100 percent
Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Willis

Setting

Parent material: Loess

Typical profile

H1 - 0 to 6 inches: silt loam
H2 - 6 to 22 inches: silt loam
H3 - 22 to 34 inches: silt loam
H4 - 34 to 38 inches: cemented material

Properties and qualities

Slope: 8 to 15 percent
Depth to restrictive feature: 20 to 40 inches to duripan
Drainage class: Well drained
Capacity of the most limiting layer to transmit water (Ksat): Very low to moderately low (0.00 to 0.06 in/hr)
Depth to water table: More than 80 inches
Frequency of flooding: None
Frequency of ponding: None
Calcium carbonate, maximum content: 10 percent
Maximum salinity: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)
Available water capacity: Moderate (about 6.7 inches)

Interpretive groups

Land capability classification (irrigated): 4e
Land capability classification (nonirrigated): 3e
Hydrologic Soil Group: C
Ecological site: R008XY102WA
Hydric soil rating: No

Appendix IX
Washington Department of Ecology Well Logs

File Original and First Copy with
Department of Ecology
Second Copy — Owner's Copy
Third Copy — Driller's Copy

WATER WELL REPORT

STATE OF WASHINGTON

Water Right Permit No.

Start Card No. W085226

UNIQUE WELL I.D. # ACE159

(1) OWNER: Name Benito URIBE Address 4209 Thorpe Rd Moxee WA 98936

(2) LOCATION OF WELL: County YAKIMA SE 1/4 SE 1/4 Sec 18 T. 12 N. R. 21 W.M.

(2a) STREET ADDRESS OF WELL (or nearest address) PARCEL 211218-44004 R

(3) PROPOSED USE: ☒ Domestic ☐ Industrial ☐ Municipal ☐
☐ Irrigation ☐ Test Well ☐ Other ☐
☐ DeWater

(4) TYPE OF WORK: Owner's number of well (If more than one)
Abandoned ☐ New well ☒ Deepened ☐ Reconditioned ☐
Method: Dug ☐ Bored ☐
Cable ☐ Driven ☐
Rotary ☒ Jetted ☐

(5) DIMENSIONS: Diameter of well 6 inches.
Drilled 220 feet. Depth of completed well 220 ft.

(6) CONSTRUCTION DETAILS:

Casing installed: 6 Diam. from 3 ft. to 157 ft.
Welded ☒ Diam. from _____ ft. to _____ ft.
Liner installed ☐ Diam. from _____ ft. to _____ ft.
Threaded ☐ Diam. from _____ ft. to _____ ft.

Perforations: Yes ☐ No ☒

Type of perforator used _____

SIZE of perforations _____ in. by _____ in.

_____ perforations from _____ ft. to _____ ft.

_____ perforations from _____ ft. to _____ ft.

_____ perforations from _____ ft. to _____ ft.

Screens: Yes ☐ No ☒

Manufacturer's Name _____

Type _____ Model No. _____

Diam. _____ Slot size _____ from _____ ft. to _____ ft.

Diam. _____ Slot size _____ from _____ ft. to _____ ft.

Gravel packed: Yes ☐ No ☒ Size of gravel _____

Gravel placed from _____ ft. to _____ ft.

Surface seal: Yes ☒ No ☐ To what depth? 20 ft.

Material used in seal Bentonite

Did any strata contain unusable water? Yes ☐ No ☒

Type of water? _____ Depth of strata _____

Method of sealing strata off _____

(7) PUMP: Manufacturer's Name _____ H.P. _____

(8) WATER LEVELS: Land-surface elevation above mean sea level _____ ft.

Static level 178 ft. below top of well Date 8-12-96

Artesian pressure _____ lbs. per square inch Date _____

Artesian water is controlled by _____ (Cap, valve, etc.)

(9) WELL TESTS: Drawdown is amount water level is lowered below static level

Was a pump test made? Yes ☐ No ☒ If yes, by whom? _____

Yield: 35 gal./min. with _____ ft. drawdown after _____ hrs.

" ESTIMATED AIRLIFT "

" " " "

Recovery data (time taken as zero when pump turned off) (water level measured from well top to water level)

Time Water Level Time Water Level Time Water Level

Date of test _____

Bailer test _____ gal./min. with _____ ft. drawdown after _____ hrs.

Airtest _____ gal./min. with stem set at _____ ft. for _____ hrs.

Artesian flow _____ g.p.m. Date _____


Temperature of water _____ Was a chemical analysis made? Yes ☐ No ☒

(10) WELL LOG or ABANDONMENT PROCEDURE DESCRIPTION

Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of information.

| MATERIAL | FROM | TO |
|----------------------------|------|-----|
| Topsoil BROWN SOFT | 0 | 3 |
| Sandstone BROWN Med | 3 | 45 |
| Clay Tan + BROWN SOFT | 45 | 92 |
| Cemented Gravel BROWN Med | 92 | 95 |
| Sandstone Tan med | 95 | 148 |
| Cemented gravel brown hard | 148 | 189 |
| Sandstone BROWN Med | 189 | 220 |

6" Drive Shoe Utilized



Work Started July 17 1996 Completed August 12 1996

WELL CONSTRUCTOR CERTIFICATION:

I constructed and/or accept responsibility for construction of this well, and its compliance with all Washington well construction standards. Materials used and the information reported above are true to my best knowledge and belief.

NAME WILLYS WELLS INC
(PERSON, FIRM, OR CORPORATION) (TYPE OR PRINT)

Address 6520 Postma Rd Yakima WA 98901

(Signed) Chris Hayes License No. 1908
(WELL DRILLER) (Chris Hayes)

Contractor's Registration No. WILLY W1088mw Date September 12 1996

(USE ADDITIONAL SHEETS IF NECESSARY)

Ecology is an Equal Opportunity and Affirmative Action employer. For special accommodation needs, contact the Water Resources Program at (206) 407-6600. The TDD number is (206) 407-6006.

TAX PARCEL NO

ECY 050-1-20 (11/98)